

5748481-5 Product Details



5748481-5



Standard Board Mount Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Number of Positions = 26
- Receptacle
- PCB Mount Angle = Right Angle
- Product Series = HD-22
- With Mating Connector Lock

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• AMPLIMITE HD-22 26 POS RECEPTACLE, RIGHT ANGLE (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• AMPLIMITE* HD-22 Front Metal Shell, PCB Mounted Conn... (PDF, English)

Application Specifications:

• <u>AMPLIMITE HD-22 Right-Angle Front Metal Shell Connectors</u> (PDF, English)

Instruction Sheets:

• None Available

CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version C)
- <u>3D Model</u> (IGES, Version C)
- 3D Model (STEP, Version C)

Additional Information:

• Product Line Information

Additional Product Images:

• Product Photo

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Number of Positions</u> = 26
- Gender = Receptacle
- PCB Mount Angle = Right Angle
- Product Series = HD-22
- Mating Connector Lock = With
- Mating Connector Lock Type = Threaded Inserts
- PCB Retention Feature = Yes
- Shell Type = Front Metal Shell
- Shell Size = 2
- Footprint (mm [in]) = 8.89 [.350]
- <u>PCB Thickness (in [mm])</u> = 0.062 [1.57]
- Grounding Indents = Without
- Grounding Straps = Without
- PCB Mount Style = Thru Hole
- Color Code = None
- Sealed = No
- Mounting Hole Diameter (mm [in]) = 3.18 [.125]
- Shell Material = Steel
- Threaded Insert Material = Zinc
- Eyelet Material = Brass

Mechanical Attachment:

• Panel Attachment = Without

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
© 2007 Tyco Electronics Corporation All Rights Reserved

Termination Related Features:

- Grounding Clips = Without
- Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]
- Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- PCB Retention Method = Boardlock(s)
- Shell Plating = Tin
- Threaded Insert Plating = Clear Chromate
- Eyelet Plating = Tin

Contact Related Features:

- Contact Mating Area Plating = Gold (30)
- Contact Material = Phosphor Bronze

Housing Related Features:

- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

• Brand = AMP