

[Skip to content](#)

Search By: Part Number Text [Tips](#)



Sunday, September 10, 2006

[Sign In](#)

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details

## Product Details for MICROSMD150F-2



### MICROSMD150F-2

Tyco Part Number: E16039-000



[Active](#)

### PolySwitch Resettable Devices



[RoHS Compliant](#)

#### Product Highlights:

- Surface Mount Application
- Family Name = microSMD
- Surface Mount Construction
- IH (Room Temperature) = 1.5 Amps.
- IT (Room Temperature) = 3.00 Amps.

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [microSMD150F](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

[List all Documents](#)

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

**Product Type Features:**

- [UL Recognized](#) = 180800-E74889

**Electrical Characteristics:**

- [IH \(Room Temperature\) \(Amps.\)](#) = 1.5
- [IT \(Room Temperature\) \(Amps.\)](#) = 3.00
- [Vmax Operating \(V\)](#) = 6
- [Rmin \( \)](#) = 0.04
- [R1 Max \[Post Trip\] \( \)](#) = 0.11
- [UL Rated Current \(Amps.\)](#) = 40
- [Tripped Power Dissipation \(Typical\) \(W\)](#) = 0.80

**Termination Related Features:**

- [Construction](#) = Surface Mount

**Body Related Features:**

- [CSA File No.](#) = 1031175 (CA 78165-1)

**Contact Related Features:**

- [Family Name](#) = microSMD

**Configuration Related Features:**

- [Form Factor \(inches\)](#) = 1210
- [Form Factor \(mm\)](#) = 3225

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant
- [TUV Certificate No.](#) = R72041438

**Conditions for Usage:**

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

**Operation/Application:**

- [Application](#) = Surface Mount

**Packaging Related Features:**

- [Packaging Method](#) = Tape & Reel

**Other:**

- [Brand](#) = Raychem

**Languages:** English | [Deutsch](#) | [Español](#) | [Português \(do Brasil\)](#) | \_\_\_\_\_ | [Italiano](#) | [正體中文 \(繁體\)](#) | [中文 \(简体\)](#) | [日本語](#)

**Country Sites:** [China](#) | [Japan](#)

© 2006 Tyco Electronics All Rights Reserved

[Home](#) | [Customer Support](#) | [Supplier](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)