<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>PolySwitch Resettable Devices</u> > <u>Product Feature Selector</u> > Product Details

# **MICROSMD175F-2** Product Details

	PolySwitch Resettable Devices
ŝ	Always EU RoHS/ELV Compliant (Statement of Compliance)
Product Highlights:	
	Surface Mount Application
	• Family Name = microSMD
MICROSMD175F-2	<ul> <li>Surface Mount Construction</li> <li>IH (Room Temperature) = 1.75 Amps.</li> </ul>
TE Part Number: A00055-000	<ul> <li>II (Room Temperature) = 1.75 Amps.</li> <li>IT (Room Temperature) = 3.50 Amps.</li> </ul>
Active	View all Features   Find Similar Products

# **Documentation & Additional Information**

# **Product Drawings:**

• microSMD175F (PDF, English)

# Catalog Pages/Data Sheets:

• None Available

# **Product Specifications:**

None Available

### **Application Specifications:**

• None Available

### Instruction Sheets:

None Available

# CAD Files:

• None Available

Additional Information:

Product Line Information

# **Related Products:**

<u>Tooling</u>

List all Documents

Product Features (Please use the Product Drawing for all design activity)

### **Product Type Features:**

- UL Recognized = 20040707-E74889
- CSA File No. = 1031175 (CA 78165-1)

# **Electrical Characteristics:**

- <u>IH (Room Temperature) (Amps.)</u> = 1.75
- <u>IT (Room Temperature) (Amps.)</u> = 3.50
- <u>Vmax Operating (V)</u> = 6
- <u>Rmin (•)</u> = 0.02
- <u>R1 Max [Post Trip] (•)</u> = 0.08
- <u>UL Rated Current (Amps.)</u> = 40
- Tripped Power Dissipation (Typical) (W) = 0.80

# **Termination Related Features:**

• Construction = Surface Mount

# **Contact Related Features:**

• <u>Family Name</u> = microSMD

# **Configuration Related Features:**

- Form Factor (inches) = 1210
- <u>Form Factor (mm)</u> = 3225

# **Industry Standards:**

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041438

#### Conditions for Usage:

• <u>Operating Temperature (Max.) (°C)</u> = 85

#### **Operation/Application:**

• Application = Surface Mount

# Packaging Related Features:

• Packaging Method = Tape & Reel

## Other:

• Brand = Raychem