SMD075F/60-2 Product Details



SMD075F/60-2

TE Part Number: C01546-000



PolySwitch Resettable Devices



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Family Name = SMD
- Surface Mount Construction
- IH (Room Temperature) = .75 Amps.
- IT (Room Temperature) = 1.50 Amps.

View all Features | Find Similar Products

Documentation & Additional Information

Product Drawings:

• SMD075F/60 (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = 20040211-E74889
- CSA File No. = 1031175 (CA 78165-1)

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 0.75
- IT (Room Temperature) (Amps.) = 1.50
- $\underline{\text{Vmax Operating (V)}} = 60$
- Rmin (•) = 0.35
- <u>R1 Max [Post Trip]</u> (•) = 1.00
- <u>UL Rated Current (Amps.)</u> = 10
- Tripped Power Dissipation (Typical) (W) = 1.70

Termination Related Features:

 $\bullet \quad Construction = Surface \ Mount \\$

Contact Related Features:

• Family Name = SMD

Configuration Related Features:

- Form Factor (inches) = 2920
- <u>Form Factor (mm)</u> = 7555

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not reviewed for lead free solder process
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041427

Conditions for Usage:

• Operating Temperature (Max.) (°C) = 85

Operation/Application:

• Application = Surface Mount

Packaging Related Features:

• Packaging Method = Tape & Reel

Other:

• Brand = Raychem