SMD150F/33-2 Product Details



SMD150F/33-2

TE Part Number: E07221-000



PolySwitch Resettable Devices



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Family Name = SMD
- Surface Mount Construction
- IH (Room Temperature) = 1.5 Amps.
- IT (Room Temperature) = 3.00 Amps.

View all Features | Find Similar Products

Documentation & Additional Information

Product Drawings:

• SMD150F/33 (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = 191099-E74889
- CSA File No. = 1031175 (CA 78165-1)

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 1.5
- IT (Room Temperature) (Amps.) = 3.00
- <u>Vmax Operating (V)</u> = 33
- $\underline{\text{Rmin}} \ (\bullet) = 0.08$
- <u>R1 Max [Post Trip]</u> (•) = 0.23
- UL Rated Current (Amps.) = 40
- Tripped Power Dissipation (Typical) (W) = 1.90

Termination Related Features:

• Construction = Surface Mount

Contact Related Features:

• Family Name = SMD

Configuration Related Features:

- Form Factor (inches) = 3425
- <u>Form Factor (mm)</u> = 8763

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041427

Conditions for Usage:

• Operating Temperature (Max.) (°C) = 85

Operation/Application:

• Application = Surface Mount

Packaging Related Features:

• Packaging Method = Tape & Reel

Other:

• Brand = Raychem