

## <u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Product Feature Selector</u> > Product Details

## 200821-1 Product Details



Documentation & Additional Information		
Product Drawings: • KEYING PLUG CONTACT SIZE 16 & 20, M SERIES (PDF, English)	Related Products: • Tooling	
Catalog Pages/Data Sheets: <ul> <li>Automachine and General Products (PDF, English)</li> <li>INTERCONNECTS FOR NETWORKING (PDF, English)</li> <li>AMP SEALED CONNECTORS (PDF, English)</li> <li>M_SERIES_PIN_AND_SOCKET_CONNECTORS (PDF, English)</li> <li>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER (PDF, English)</li> <li>SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY</li> </ul>		
(PDF, English) Product Specifications:  • None Available Application Specifications:		
<ul> <li><u>Ferrules For M Series Connectors</u> (PDF, English)</li> <li>Instruction Sheets:         <ul> <li><u>Accessories for Circular Plastic Connectors (CPC)</u> (PDF, English)</li> </ul> </li> </ul>		
<ul> <li>CAD Files: (CAD Format &amp; Compression Information)</li> <li><u>2D Drawing</u> (DXF, Version H)</li> <li><u>3D Model</u> (IGES, Version H)</li> <li><u>3D Model</u> (STEP, Version H)</li> </ul>		
List all Documents		

Product Features (Please use the Product Drawing for all design activity)		
<ul> <li>Product Type Features: <ul> <li>Product Type = Keying Plug</li> <li>Connector Line = Commercial MATE-N-LOK</li> <li>Color = Natural</li> <li>Comment = Snaps into socket housing.</li> </ul> </li> <li>Body Related Features: <ul> <li>Flammability Rating = UL 94V-2</li> </ul> </li> </ul>	<ul> <li>Housing Related Features: <ul> <li>Housing Material = Nylon</li> </ul> </li> <li>Industry Standards: <ul> <li>RoHS/ELV Compliance = RoHS compliant, ELV compliant</li> <li>Lead Free Solder Processes = Not relevant for lead free process</li> <li>RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul> </li> <li>Other: <ul> <li>Brand = AMP</li> </ul> </li> </ul>	