



NON-CONTACT VOLTAGE TESTERS

[Product Index](#) > [Electrical Testers](#) > [Circuit and Voltage Testers](#) > [Non-Contact Voltage Testers](#) > **NCVT-2**

Dual Range Non-Contact Voltage Tester - NCVT-2

- Automatically detects and indicates low voltage (12-48V AC) and standard voltage (48-1000V AC) allowing broad application.
- Non-contact detection of standard voltage in cables, cords, circuit breakers, lighting fixtures, switches, outlets and wires.
- Non-contact detection of low voltage in security, entertainment, communications, environmental control, and irrigation systems.
- High intensity, bright green LED indicates the tester is operational and aids in illuminating the workspace.
- Digitally controlled ON/OFF power button.
- Auto power-off feature conserves and extends battery life.
- Microprocessor controlled low-battery indicator.
- CAT IV 1000 Volt rating provides expanded operation and protection.
- Lightweight, durable polycarbonate plastic resin construction; convenient pocket clip.



Join Today!
to receive product updates!



Pictured: NCVT-2

Cat. No.	Batteries	Frequency Range	Height	Overall Length	Pollution Degree	Voltage Range	Weight w/Batteries (oz.)	Weight Per (oz.)	Width
NCVT-2	Two alkaline 1.5V AAA (included)	50-500 Hz	1.0"	5.5" (14) cm	2	12-1000 V AC	1.6	.8	.72"

All dimensions are in inches and (millimeters) except where indicated.

⚠ WARNINGS: Read, understand, and follow all warnings, cautions, safety information, and instructions in the manual before operating or servicing this tester. Failure to follow instructions could result in death or serious injury.

For questions regarding Klein Tools, please use the [Contact Klein Tools](#) page. For questions regarding Klein Tools' policy regarding the use of this site, please see our [Legal Notice/Privacy Statement](#).