

207485-1 Product Details



207485-1



CPC Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Number of Positions = 16
- Plug
- For Use With Socket Contacts
- Not Preloaded

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• PLUG ASSEMBLY, SHELL SIZE 23, STANDARD SEX, SERIES 4... (PDF, English)

Catalog Pages/Data Sheets:

- CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ... (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

Product Specifications:

• Connector, Circular Plastic (PDF, English)

Application Specifications:

• None Available

Instruction Sheets:

• Circular Plastic Connectors (CPC) (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version G)
- <u>3D Model</u> (IGES, Version G)
- 3D Model (STEP, Version G)

Additional Information:

• Product Line Information

Additional Product Images:

• Contact Arrangement

Related Products:

- Tooling
- Mating Products (3)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Product Type</u> = Connector
- Number of Positions = 16
- Gender = Plug
- For Use With = Socket Contacts
- Termination Style = Wire
- Shell Size = 23
- Shell Type = All Plastic
- Thread Size = 1-3/8 18 UNEF-2A
- Product Series = Series 4
- Sealed = No
- Number of Circuits = 4 (Power)/12 (MultiMate)

Mechanical Attachment:

- Preloaded = No
- VDE Tested = No

Body Related Features:

- Mount Style = Free Hanging
- Insulation Diameter (Signal Conductor) (mm [in]) = 3.81 [0.150]
- Insulation Diameter (Power Conductor) (mm [in]) = 5.59 [0.220]
- Coupling Ring Material = Polyester

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2007 Tyco Electronics Corporation All Rights Reserved

Contact Related Features:

- Standard or Reverse Gender = Standard
- Coupling Ring Diameter (mm [in]) = 45.29 [1.783]

Housing Related Features:

- Housing Material = Nylon 6/6 GF
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

Configuration Related Features:

• Reverse Numbering = Without

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

Brand = AMP