



206613-3 Product Details



206613-3

[Active](#)

CPC Connectors



[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- Connector
- Number of Positions = 22
- Receptacle
- For Use With Pin Contacts
- Not Preloaded

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [RECEPTACLE HOUSING, STANDARD SEX, SHELL SIZE 23, CPC](#) (PDF, English)

Catalog Pages/Data Sheets:

- [CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...](#) (PDF, English)
- [AMP Circular Connectors for Commercial Signal & Powe...](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- [Circular Plastic Connectors \(CPC\)](#) (PDF, English)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version P1)
- [3D Model](#) (IGES, Version P1)
- [3D Model](#) (STEP, Version P1)

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Contact Arrangement](#)

Related Products:

- [Tooling](#)
- [Mating Products \(2\)](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Number of Positions](#) = 22
- [Gender](#) = Receptacle
- For Use With = Pin Contacts
- Termination Style = Wire
- [Shell Size](#) = 23
- [Shell Type](#) = All Plastic
- [Thread Size](#) = 1-3/8 - 18 UNEF-2A
- [Product Series](#) = Series 4
- [Sealed](#) = No
- Number of Circuits = 2 (Power)/20 (MultiMate)

Mechanical Attachment:

- [Preloaded](#) = No
- [VDE Tested](#) = No

Body Related Features:

- [Mount Style](#) = Free Hanging
- Insulation Diameter (Signal Conductor) (mm [in]) = 3.81 [0.150]
- Insulation Diameter (Power Conductor) (mm [in]) = 5.59 [0.220]

Contact Related Features:

- [Standard or Reverse Gender](#) = Standard

Housing Related Features:

- Housing Material = Thermoplastic
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

Configuration Related Features:

- [Reverse Numbering](#) = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved