

164164-2

TE Internal Number: 164164-2

Active

Multimate

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Pin
- Gold (30) over Nickel (50) Contact Mating Area Plating Material
- Wire Range = 0.80-1.40² [18-16] mm [AWG]
- Insulation Diameter = 2.01 2.49 mm
- Copper Alloy Contact Base Material

View all Features

Documentation & Additional Information

Product Drawings:

• loose piece pin type 3+ contact size 16 (PDF, English)

Catalog Pages/Data Sheets:

- PRECISION PIN AND SOCKET CONTACTS (PDF, English)
- Signal Contacts (PDF, English)
- M_SERIES_PIN_AND_SOCKET_CONNECTORS (PDF, English)
- <u>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...</u> (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Pin/Socket</u> = Pin
- <u>Insulation Diameter (mm [in])</u> = 2.01 2.49
 [0.079 0.098]
- Product Type = Type III+
- <u>Insulation Support</u> = Yes
- Wire Termination Type = Crimp
- Wire/Cable Type = Regular Wire
- Grade = Commercial
- Make First / Break Last = Yes
- Comment = Leading Pin (1.8mm longer than standard pins); Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125].

Electrical Characteristics:

High Current = No

Termination Related Features:

- <u>Termination End Plating</u> = Gold Flash
- Pin Diameter (mm [in]) = 1.57 [0.062]

Body Related Features:

Contact Related Features:

- <u>Contact Mating Area Plating Material</u> = Gold
 (30) over Nickel (50)
- Contact Base Material = Copper Alloy
- Contact Size = 16
- Contact Type = Grounding

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- <u>Terminate To</u> = Wire
- Test Current (Amps.) = 13.0

Packaging Related Features:

- Packaging Method = Loose Piece
- Packaging Quantity = 200

Other:

•	Wire Range (mn	<u>n [AWG])</u> =	= 0.80-1.402	[18-
	16]			

- Spring Material = Stainless Steel
- Used With = CPC Connectors

• Brand = AMP