

66590-1

TE Internal Number: 66590-1



Multimate



Product Highlights:

- Socket
- Tin Contact Mating Area Plating Material
- Wire Range = 0.80-1.40² [18-16] mm [AWG]
- Insulation Diameter = 2.03 2.54 mm
- Brass Contact Base Material

View all Features

Documentation & Additional Information

Product Drawings:

 CONTACT, SOCKET, LOOSE PIECE, TYPE VI, MULTIMATE (PDF, English)

Catalog Pages/Data Sheets:

• AEROSPACE & DEFENSE (PDF, English)

Product Specifications:

None Available

Application Specifications:

• Type VI Insulation Grip Contacts (PDF, English)

Instruction Sheets:

- <u>Selection Charts for Multimate Pin and Socket Contacts</u> (PDF, English)
- Application and Maintenance for Crimping Head Assembly (PDF, English)

CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version G)
- 3D Model (IGES, Version G)
- 3D Model (STEP, Version G)

<u>List all Documents</u>

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Pin/Socket = Socket
- <u>Insulation Diameter (mm [in])</u> = 2.03 2.54
 [0.080 0.100]
- Product Type = Type VI
- Insulation Support = Yes
- Wire Termination Type = Crimp
- Wire/Cable Type = Discrete Wire
- Grade = Commercial
- Comment = Wire strip length-- 3.96 [.156] for all wire sizes.

Electrical Characteristics:

High Current = No

Termination Related Features:

- <u>Termination End Plating</u> = Tin
- Pin Diameter (mm [in]) = 1.57 [0.062]

Body Related Features:

- Wire Range (mm [AWG]) = 0.80-1.40² [18-16]
- Spring Material = Stainless Steel
- Used With = G Series Connectors

Contact Related Features:

- Contact Mating Area Plating Material = Tin
- Contact Base Material = Brass
- Contact Size = 16
- Contact Type = Signal

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Wire
- Test Current (Amps.) = 13.0

Packaging Related Features:

• Packaging Method = Loose Piece

Other:

• Brand = AMP