

1658643-1 Product Details



1658643-1

TE Internal Number: 1658643-1 <u>Active</u> Niew 3D PDF

Standard Cable Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector Product Series = HDP-20 (Crimp Snap)
- 9 Positions Without Enclosure
- Connector Style = Receptacle View all Features
- **Documentation & Additional Information Product Drawings:** Additional Information: RECEPTACLE CONNECTOR, SIZE 1, 9 POSN, WITH CLINCH NU... (PDF, English) Product Line Information **Related Products:** Catalog Pages/Data Sheets: AMPLIMITE Subminiature D Connectors - Cable Connectors (PDF, English) ٠ <u>Tooling</u> Mating Products (11) **Product Specifications:** <u>AMPLIMITE* HDP-20 Subminiature D Connector With F Cr...</u> (PDF, English) Application Specifications: AMPLIMITE HDP-20 and Economy Crimp Snap Subminiature... (PDF, English) Instruction Sheets: • AMPLIMITE High Density (HDP-20) Connectors with Crim... (PDF, English) CAD Files: (<u>CAD Format & Compression Information</u>) • <u>2D Drawing</u> (DXF, Version O) • <u>3D Model</u> (IGES, Version O) • <u>3D Model</u> (STEP, Version O) List all Documents

Product Features (Please use the Product Drawing for all design activity) **Product Type Features: Contact Related Features:** Product Type = Connector Preloaded = No Product Series = HDP-20 (Crimp Snap) • Contact Size = 20 <u>Mating Connector Lock</u> = With • Mating Connector Lock Type = Clinch Nut, 4-40 UNC Housing Related Features: Enclosure = Without • Shell Size = 1 • Connector Style = Receptacle • <u>Shell Type</u> = Full Metal Shell • Grounding Indents = Without Industry Standards: Grade = Standard • <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant Color = Black • Lead Free Solder Processes = Not relevant for lead free Shell Material = Steel process • RoHS/ELV Compliance History = Always was RoHS compliant **Body Related Features:** Number of Positions = 9 Other: • Shell Plating = Tin • Brand = AMP • Insert Material = Thermoplastic

• Comment = Clinch Nut: 4-40 threads with self-locking feature; Receptacles accept size 20 DF socket contacts.

• Insert Flammability Rating = UL 94V-0