

1658659-1 Product Details



1658659-1



Standard Cable Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector Kit
- Product Series = HDP-20 (Crimp Snap)
- Number of Positions = 25
- Shielded
- Plug

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• BULK KIT, PLUG, SHIELDING ENCLOSURE, SIZE 3, 25 POSN... (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• AMPLIMITE* HDP-20 Subminiature D Connector With F Cr... (PDF, English)

Application Specifications:

• AMPLIMITE HDP-20 & Econo Crimp Snap Subminiature D C... (PDF, English)

Instruction Sheets:

- Shielding Hardware Kits w/AMPLIMITE hde-20 hdp-20 an... (PDF, English)
- Shielding Hardware Enc Kits w/AMPLIMITE HDE-20 HDP-2... (PDF, English)
- AMP* INSERTION/EXTRACTION TOOL 91285-1 AND REPLACEME... (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version O)
- <u>3D Model</u> (IGES, Version O)
- <u>3D Model</u> (STEP, Version O)

Additional Information:

• Product Line Information

Related Products:

- Tooling
- Mating Products (9)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector Kit
- Product Series = HDP-20 (Crimp Snap)
- Number of Positions = 25
- Shielded = Yes
- Gender = Plug
- Mating Connector Lock = With
- Mating Connector Lock Type = Jackscrews
- Shell Size = 3
- Shell Type = Full Metal Shell
- Grounding Indents = With
- Grade = Standard
- Enclosure Material = PVC
- Jackscrew Material = Zinc Alloy
- Color = Black
- Shell Material = Steel
- Shield Material = Steel
- Comment = Plugs accept size 20 DF pin contacts.; Maximum cable diameter
 after jacket and braid removed.; There is a maximum Cable O.D. of 11.56
 [.455] for Shielding Enclosure Expansion Tool 58241-1.

Body Related Features:

- Pre-Assembled = No
- <u>Cable Insulation Diameter (mm [in])</u> = 5.51 11.05 [0.217 0.435]
- Shell Plating = Tin
- Shield Plating = Tin over Copper
- Insert Material = Thermoplastic
- Insert Flammability Rating = UL 94V-0
- Cable Diameter (Max.) (mm [in]) = 8.89 [0.350]

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
© 2007 Tyco Electronics Corporation All Rights Reserved

Contact Related Features:

- Contacts = Without
- Contact Size = 20

Housing Related Features:

- Housing Material = Nylon
- Housing Flammability Rating = UL 94V-0
- Housing Color = Black

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- Packaging Method = Bulk
- Packaging Quantity = 100

Other:

• Brand = AMP