


205170-1 Product Details



205170-1



Subminiature D Pin/Socket Connectors for MIL-C-24308 and MIL-C-39029

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

- Connector
- Product Series = 109
- Density = Standard
- Terminate To Wire
- Number of Positions = 50

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• AMPLIMITE PLUG FOR PIN CONTACTS HI-DENSITY HD-20 CON... (PDF, English)

Catalog Pages/Data Sheets:

• <u>AEROSPACE & DEFENSE</u> (PDF, English)

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Additional Product Images:

• Insert Arrangement

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Product Type</u> = Connector
- Product Series = 109
- Number of Positions = 50
- Gender = Plug
- Shell Size = 5
- Shell Material = Steel
- Wire Termination Type = Crimp
- Mounting Hole Diameter (mm [in]) = 3.05 [.120]

Body Related Features:

- Blindmate = No
- Non-Magnetic = No
- $\underline{Pins} = Without$
- Rear Grommet = No
- Power/Signal/Coax Combination = No
- Shell Plating = Cadmium
- Mount Style = Mounting Holes
- Retention Clip Material = Stainless Steel

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2007 Tyco Electronics Corporation All Rights Reserved

Contact Related Features:

- Contact Size = 20
- Contact Style = Crimp Snap-in

Configuration Related Features:

• Density = Standard

Industry Standards:

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M24308/4-263F
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- NASA Qualification = No

Conditions for Usage:

• Terminate To = Wire

Other:

• Brand = AMP