5745781-3 Product Details



Documentation & Additional Information

Product Drawings:

• RCPT ASSY, SIZE 1, 9 POSN, RTANG, AMPLIMITE HD-20, W... (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

None Available

- CAD Files: (CAD Format & Compression Information)
 - <u>2D Drawing</u> (DXF, Version O)
 - <u>3D Model</u> (IGES, Version O)
 - <u>3D Model</u> (STEP, Version O)

Additional Information:

• Product Line Information

Additional Product Images:

• Product Photo

Related Products:

- <u>Tooling</u>
- Mating Products (6)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Number of Positions</u> = 9
- <u>Gender</u> = Receptacle
- <u>PCB Mount Angle</u> = Right Angle
- <u>Product Series</u> = HD 20
- <u>Mating Connector Lock</u> = With
- <u>Mating Connector Lock Type</u> = Threaded Insert, 4-40 UNC
- <u>PCB Retention Feature</u> = Yes
- <u>Shell Type</u> = Front Metal Shell
- <u>Shell Size</u> = 1
- Footprint (mm [in]) = 8.08 [.318]
- <u>PCB Thickness (in [mm])</u> = 0.093 [2.36]
- <u>Grounding Indents</u> = Without
- Grounding Straps = With
- <u>PCB Mount Style</u> = Thru Hole
- <u>Color Code</u> = None
- Sealed = No
- Profile = Standard
- Post Size (mm [in]) = 0.66 [.026]
- Mounting Hole Diameter (mm [in]) = 3.18 [.125]
- Shell Material = Steel
- Threaded Insert Material = Zinc
- Eyelet Material = Brass
- Comment = All receptacles are preloaded with size 20 DF posted socket contacts

Mechanical Attachment:

• <u>Panel Attachment</u> = Without

Provide Website Feedback | Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support © 2007 Tyco Electronics Corporation All Rights Reserved

Termination Related Features:

- <u>Grounding Clips</u> = Without
- <u>Termination (Solder) Post Length (mm [in])</u> = 3.18 [0.125]
- <u>Solder Tail Contact Plating</u> = Tin over Nickel

Body Related Features:

- <u>PCB Retention Method</u> = Mounting Holes
- Shell Plating = Tin
- Threaded Insert Plating = Clear Chromate
- Eyelet Plating = Tin

Contact Related Features:

- Contact Mating Area Plating = Gold Flash
- Contact Shape = Round
- Contact Material = Phosphor Bronze

Housing Related Features:

- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

• Brand = AMP