

5747840-6 Product Details



5747840-6

TE Internal Number: 5747840-6





Standard Board Mount Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- 9 Positions
- Housing Gender = Plug
- PCB Mount Angle = Right Angle Product Series = HD 20
- With Mating Connector Lock

Documentation & Additional Information

Product Drawings:

• PLUG ASSEMBLY, SIZE 1, 9 POS, RIGHT ANGLE, FRONT MET... (PDF, English)

Catalog Pages/Data Sheets:

AMPLIMITE Subminiature D Connectors - Right-Angle Po... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version O)
- 3D Model (IGES, Version O)
- 3D Model (STEP, Version O)

Additional Information:

Product Line Information

Related Products:

- Tooling
- Mating Products (9)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- PCB Mount Angle = Right Angle
- <u>Product Series</u> = HD 20
- <u>Mating Connector Lock</u> = With
- Mating Connector Lock Type = Female Screwlocks, Fixed
- PCB Mount Retention = With
- <u>Shell Type</u> = Front Metal Shell
- Shell Size = 1
- Footprint (mm [in]) = 8.08 [.318]
- Grounding Indents = With
- <u>Grounding Straps</u> = With
- <u>PCB Mount Style</u> = Through Hole
- <u>Color Code</u> = None
- Sealed = No
- Profile = Standard
- Post Size (mm [in]) = 0.66 [.026]
- Mounting Hole Diameter (mm [in]) = 3.18 [.125]
- Shell Material = Steel
- Eyelet Material = Brass
- Comment = Plugs are preloaded with size 20 DF posted pin contacts

Mechanical Attachment:

- <u>Panel Attachment</u> = Without
- Boardlock Material = Copper Alloy
- Boardlock Plating = Tin over Nickel
- Female Screwlock Material = Zinc
- Female Screwlock Plating = Clear Chromate

Termination Related Features:

- <u>Grounding Clips</u> = Without
- Termination Post Length (mm [in]) = 3.18 [0.125]
- Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- Number of Positions = 9
- <u>PCB Mount Retention Type</u> = Boardlock(s)
- Shell Plating = Tin
- Eyelet Plating = Tin over Copper Flash

Contact Related Features:

- <u>Contact Plating, Mating Area, Material</u> = Gold (30)
- Contact Shape = Round
- Contact Base Material = Brass

Housing Related Features:

- Housing Gender = Plug
- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic GF

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• PCB Thickness (in [mm]) = 0.062 [1.57]

Other:

Brand = AMP