


5747460-3 Product Details



5747460-3



Standard Board Mount Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Number of Positions = 15
- Receptacle
- PCB Mount Angle = Right Angle
- Product Series = HD 20
- With Mating Connector Lock

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• RECEPTACLE ASSY, SIZE 2, 15 POSN, RIGHT ANGLE, .590 ... (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Number of Positions</u> = 15
- Gender = Receptacle
- PCB Mount Angle = Right Angle
- Product Series = HD 20
- Mating Connector Lock = With
- Mating Connector Lock Type = Threaded Inserts
- PCB Retention Feature = Yes
- Shell Type = All Plastic
- Shell Size = 2
- Footprint (mm [in]) = 14.99 [.590]
- PCB Thickness (in [mm]) = 0.093 [2.36]
- Grounding Indents = Without
- Grounding Straps = Without
- PCB Mount Style = Thru Hole
- Color Code = None
- Sealed = No
- Profile = Standard
- Post Size (mm [in]) = 0.66 [.026]
- Mounting Hole Diameter (mm [in]) = 3.18 [.125]
- Threaded Insert Material = Zinc
- Comment = All receptacles are preloaded with size 20 DF posted socket contacts

Mechanical Attachment:

• Panel Attachment = Without

Termination Related Features:

- Grounding Clips = Without
- Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]
- Solder Tail Contact Plating = Tin over Nickel

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
© 2007 Tyco Electronics Corporation All Rights Reserved

Body Related Features:

- PCB Retention Method = Mounting Holes
- Threaded Insert Plating = Clear Chromate

Contact Related Features:

- Contact Mating Area Plating = Gold Flash
- Contact Shape = Round
- Contact Material = Phosphor Bronze

Housing Related Features:

- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

• Application = Standard

Other:

• Brand = AMP