



745203-9 Product Details



745203-9

[Active](#)

Standard Cable Connectors



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Connector
- Product Series = HDE-20 (IDC)
- Number of Positions = 9
- Plug
- With Contacts

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [PLUG ASSEMBLY, SIZE 1, 9 POSITION, AMPLIMITE](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [Connector, AMPLIMITE HDE-20, Insulation Displacement](#) (PDF, English)

Application Specifications:

- [AMPLIMITE HDE-20 IDC Connectors](#) (PDF, English)

Instruction Sheets:

- [AMPLIMITE High-Density \(HDE-20\) Insulation Displacement...](#) (PDF, English)

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version S)
- [3D Model](#) (IGES, Version S)
- [3D Model](#) (STEP, Version S)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)
- [Mating Products \(26\)](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Product Series](#) = HDE-20 (IDC)
- Number of Positions = 9
- [Gender](#) = Plug
- [Wire/Cable Type](#) = Discrete Wire, Round Jacketed Cable
- [Wire Termination Type](#) = Insulation Displacement Crimp (IDC)
- [Wire Insulation Diameter \(mm \[in\]\)](#) = 1.52 [0.060]
- [Mating Connector Lock](#) = With
- [Mating Connector Lock Type](#) = Mounting Holes
- [Shell Size](#) = 1
- [Shell Type](#) = All Plastic
- [Grounding Indents](#) = Without
- Grade = Standard
- Color = Black
- Comment = All connectors are preloaded. Individual conductor strands should be larger than 0.13 [.005] diameter. Contacts accept a max. wire insulation thickness of 0.38 [.015]. HDE connectors are designed for terminating solid or stranded (7-strand max.) wire.; HDE connectors are designed for terminating solid or stranded (7-strand max.) wire.; Individual conductor strands should be larger than 0.127 in. [.005] diameter.

Termination Related Features:

- [Solder Tail Contact Plating](#) = Tin over Nickel

Body Related Features:

- [Wire Range \(mm² \[AWG\]\)](#) = 0.15 - 0.40 [26-22]

Contact Related Features:

- [Contacts](#) = With
- [Contact Mating Area Plating](#) = Gold Flash over Palladium Nickel or Gold (30) over Nickel
- [Contact Size](#) = 20
- Contact Material = Phosphor Bronze

Housing Related Features:

- Housing Material = Thermoplastic
- Housing Flammability Rating = UL 94V-0

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved