


749806-7 Product Details



749806-7



Standard Cable Connectors



Product Highlights:

- Cable Connector and Clamp
- Product Series = HDP-20 (Crimp Snap)
- Number of Positions = 9
- Shielded
- Receptacle

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• RECEPTACLE KIT, UNASSEMBLED, SIZE 1, 9 POSN, METAL S... (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• AMPLIMITE* HDP-20 Subminiature D Connector With F Cr... (PDF, English)

Application Specifications:

- HD-20 Precision Formed Contacts (PDF, English)
- AMPLIMITE HDP-20 & Econo Crimp Snap Subminiature D C... (PDF, English)

Instruction Sheets:

- AMPLIMITE Connector HD-20 Shielded Cable Clamp Kits (PDF, English)
- AMPLIMITE High Density (HDP-20) Connectors with Crim... (PDF, English)
- PRO-CRIMPER II Hand Tool Assembly 58448-2 With Die A... (PDF, English)
- AMP* INSERTION/EXTRACTION TOOL 91285-1 AND REPLACEME... (PDF, English)

CAD Files:

None Available

List all Documents

Additional Information:

• Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Cable Connector and Clamp
- Product Series = HDP-20 (Crimp Snap)
- Number of Positions = 9
- Shielded = Yes
- Gender = Receptacle
- Wire Termination Type = Crimp Snap
- Mating Connector Lock = With
- Mating Connector Lock Type = Mounting Holes
- Shell Size = 1
- Shell Type = Full Metal Shell
- Grounding Indents = Without
- Grade = Standard
- Cable Clamp Type = One-Piece Quick Snap
- \bullet Grommets = With
- Screws and Retainer Clips = With
- Body Material = Polypropylene
- Cable Support Gate Material = Polypropylene
- Shell Material = Steel
- Retainer Clip Material = Stainless Steel
- Strain Relief Clip Material = Stainless Steel
- Screw Material = Steel

Mechanical Attachment:

- Mounting Screw Material = Steel
- Mounting Screw Plating = Zinc
- Screw Plating = Zinc

Termination Related Features:

• Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- Wire Range (mm² [AWG]) = 0.2 0.56 [24-20]
- Cable Insulation Diameter (mm [in]) = 4.70 8.13 [0.185 0.320]
- Cable Exit Angle = Straight(180°)
- Shell Plating = Tin over Copper

Contact Related Features:

- $\underline{Contacts} = With$
- Contact Mating Area Plating = Gold Flash
- Contact Size = 20
- Contact Material = Phosphor Bronze, Brass

Housing Related Features:

- Housing Material = Nylon, Polyester GF
- Housing Flammability Rating = UL 94V-0
- Housing Color = Black

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- Packaging Method = Bulk
- Packaging Quantity = 100

Other:

• Brand = AMP