

# 5749771-1 Product Details



5749771-1



#### **Standard Board Mount Connectors**



Always EU RoHS/ELV Compliant (Statement of Compliance)

# **Product Highlights:**

- Number of Positions = 44
- Plug
- PCB Mount Angle = Right Angle
- Product Series = HD-22
- With Mating Connector Lock

View all Features | Find Similar Products



#### **Documentation & Additional Information**

### **Product Drawings:**

• AMPLIMITE HD-22 44 POS PLUG, RIGHT ANGLE (PDF, English)

# Catalog Pages/Data Sheets:

• None Available

## **Product Specifications:**

• AMPLIMITE\* HD-22 Front Metal Shell, PCB Mounted Conn... (PDF, English)

#### **Application Specifications:**

• AMPLIMITE HD-22 Right-Angle Front Metal Shell Connectors (PDF, English)

## **Instruction Sheets:**

• None Available

### **CAD Files:**

• None Available

#### Documentation & Additional Information

## **Additional Information:**

• Product Line Information

## **Additional Product Images:**

• Product Photo

# **Related Products:**

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

#### **Product Type Features:**

- Number of Positions = 44
- Gender = Plug
- PCB Mount Angle = Right Angle
- Product Series = HD-22
- Mating Connector Lock = With
- Mating Connector Lock Type = Threaded Inserts
- PCB Retention Feature = Yes
- Shell Type = Front Metal Shell
- Shell Size = 3
- Footprint (mm [in]) = 8.08 [.318]
- <u>PCB Thickness (in [mm])</u> = 0.062 [1.57]
- Grounding Indents = With
- Grounding Straps = Without
- PCB Mount Style = Thru Hole
- Color Code = None
- Sealed = No
- Shell Material = Steel
- Threaded Insert Material = Zinc
- Eyelet Material = Brass

#### **Mechanical Attachment:**

- Panel Attachment = Without
- Boardlock Material = Copper Alloy
- Boardlock Plating = Tin over Nickel

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2007 Tyco Electronics Corporation All Rights Reserved

#### **Termination Related Features:**

- Grounding Clips = Without
- Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]
- Solder Tail Contact Plating = Tin over Nickel

#### **Body Related Features:**

- PCB Retention Method = Boardlock(s)
- Shell Plating = Tin
- Threaded Insert Plating = Clear Chromate
- Eyelet Plating = Tin over Copper Flash

#### **Contact Related Features:**

- Contact Mating Area Plating = Gold (30)
- Contact Material = Copper Alloy

#### **Housing Related Features:**

- Housing Flammability Rating = UL 94V-0
- Housing Material = Thermoplastic

#### **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Other:

Brand = AMP