


3-1734285-3 Product Details



3-1734285-3



Stacked Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector Configuration [Upper Conn./Lower Conn.] = Same Series
- Receptacle over Receptacle
- Mating Connector Lock Type = Threaded Insert, 4-40 UNC
- Without Mating Polarization
- Yes PCB Retention Feature

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• D-SUB STACKED RCPT. OVER RCPT., R/A TYPE, THREAD INS... (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

None Available

Instruction Sheets:

• None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version O)
- <u>3D Model</u> (IGES, Version O)
- 3D Model (STEP, Version O)

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Gender = Receptacle over Receptacle
- Mating Connector Lock Type = Threaded Insert, 4-40 UNC
- Mating Polarization = Without
- PCB Retention Feature = Yes
- Stacked Number of Positions [Upper Conn./Lower Conn.] = 37/37
- Shell Type = Front Metal Shell
- Product Series = Series III
- Color Code = None
- Pin/Socket = Pin (Upper)/Pin (Lower)
- PCB Mount Angle = Right Angle
- Shell Material = Steel

Mechanical Attachment:

- Boardlock Material = Copper Alloy
- Boardlock Plating = Tin

Termination Related Features:

- Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]
- Solder Tail Contact Plating = Bright Tin over Nickel

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2007 Tyco Electronics Corporation All Rights Reserved

Body Related Features:

- Connector Configuration [Upper Conn./Lower Conn.] = Same Series
- Centerline, Matrix (mm [in]) = 2.77 x 2.84 [.109 x .112]
- PCB Retention Method = Boardlock(s)

Contact Related Features:

- Contact Mating Area Plating = Gold (30)
- Contact Material = Copper Alloy

Housing Related Features:

- Housing Color = Black
- Housing Material = Thermoplastic
- Housing Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

• Brand = AMP