




## 204515-2 Product Details



**204515-2**

TE Internal Number: 204515-2



[Active](#)

### Subminiature D Pin/Socket Connectors for MIL-C-24308 and MIL-C-39029

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

**Product Highlights:**

- Connector
- Product Series = 90
- Density = High
- Terminate To Wire
- 26 Positions

[View all Features](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">KIT, "HDD" SERIES PLUG, SIZE 2 (26 POSITION)</a> (PDF, English)</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">AEROSPACE &amp; DEFENSE</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">AMPLIMITE* HIGH DENSITY 22 (HD-22) CONNECTORS</a> (PDF, English)</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Type</a> = Connector</li> <li>• <a href="#">Product Series</a> = 90</li> <li>• <a href="#">Number of Positions</a> = 26</li> <li>• <a href="#">Gender</a> = Plug</li> <li>• <a href="#">Shell Size</a> = 2</li> <li>• <a href="#">Shell Material</a> = Steel</li> <li>• <a href="#">Wire Termination Type</a> = Crimp</li> <li>• Mounting Hole Diameter (mm [in]) = 3.05 [.120]</li> <li>• Comment = "F" is stamped on connectors following M24308 part number as required. "F" designates cadmium shell plating.; Size 22 pins supplied with plugs are loose piece.</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Blindmate</a> = No</li> <li>• <a href="#">Non-Magnetic</a> = No</li> <li>• <a href="#">Pins</a> = With</li> <li>• <a href="#">Rear Grommet</a> = No</li> <li>• <a href="#">Power/Signal/Coax Combination</a> = No</li> <li>• <a href="#">Shell Plating</a> = Cadmium</li> <li>• Mount Style = Mounting Holes</li> <li>• Retention Clip Material = Stainless Steel</li> </ul>	<p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Contact Size</a> = 22</li> <li>• <a href="#">Contact Style</a> = Crimp Snap-in</li> </ul> <p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Density</a> = High</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• Government/Industry Qualification = Yes</li> <li>• Government/Industry Part Number = M24308/4-12F</li> <li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not relevant for lead free process</li> <li>• NASA Qualification = No</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• Terminate To = Wire</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = AMP</li> </ul>