
5786090-7 Product Details



Documentation & Additional Information

Product Drawings:

• PLUG ASSEMBLY, UNSHIELDED, 0.635[.025] CENTERLINE, ... (PDF, English)

Catalog Pages/Data Sheets:

- None Available
- **Product Specifications:**
 - Connector, AMPLIMITE, Shielded, .050 Series (PDF, English)

Application Specifications:

• AMPLIMITE .050 Series Insulation Displacement and Pr... (PDF, English)

Instruction Sheets:

- Manual Arbor Frame Assembly 58024-1 (PDF, English)
- AMP* REPAIR TOOL 58430-1 FOR AMPLIMITE* .050-SERIES ... (PDF, English)
- AMPLIMITE .050 Series Connectors (Round-to-Flat Cable) (PDF, English)
- Installation and Use of Mass Termination Tooling (PDF, English)
- Cover Lacing Fixture 91293-1 for AMPLIMITE .050 Seri... (PDF, English)
- AMP* MANUAL MINIATURE APPLICATOR FRAME ASSEMBLY 91295-1 (PDF, English)
- Cover Closing Kits and Staple Inserter Kit (PDF, English)
- Tooling Kit 768900-1 (PDF, English)

CAD Files: (CAD Format & Compression Information)

• <u>2D Drawing</u> (DXF, Version O1)

Additional Information:

Product Line Information

Related Products:

• <u>Tooling</u>

- <u>3D Model</u> (IGES, Version O1)
- <u>3D Model</u> (STEP, Version O1)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Product Type</u> = Connector
- <u>Gender</u> = Plug
- Number of Positions = 68
- <u>Wire/Cable Type</u> = Ribbon Cable
- <u>Mating Connector Lock</u> = Without
- <u>Shielded</u> = No
- <u>Detent</u> = Without
- <u>Rails</u> = Without
- Termination Cover = With
- <u>Product Series</u> = Series III
- Wire Termination Type = IDC
- Color = Black

Mechanical Attachment:

• <u>Panel Attachment</u> = Without

Termination Related Features:

• Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- Ribbon Cable Centerline Spacing (mm [in]) = 0.64 [0.025]
- Wire Range (mm [AWG]) = 0.05² [30]
- Termination Cover Color = Black

Contact Related Features:

- Contact Material = Phosphor Bronze
- Contact Mating Area Plating = Gold (30)
- **Housing Related Features:**
 - Housing Material = PBT GF 30
 - Housing Flammability Rating = UL 94V-0

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Wire
- Packaging Related Features:
 - Packaging Method = Tube

Other:

• Brand = AMP