


# 5749070-7 Product Details



## 5749070-7

TE Internal Number: 5749070-7



### .050 Series Board Mount Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

### **Product Highlights:**

- Connector Type = Receptacle
- Number of Positions = 68 PCB Mount Angle = Vertical
- Through Hole Contact Termination Type

View all Features

Add to My Part List

Request Sample

Find Similar Products

**Buy Product** 

## **Documentation & Additional Information**

Product Drawings:

• RECEPTACLE ASSEMBLY, SHIELDED, VERTICAL, AMPLIMITE .0... (PDF, English)

Catalog Pages/Data Sheets:

• AMPLIMITE Subminiature D Connectors - .050 Series Co... (PDF, English)

Product Specifications:

◆ Connector, AMPLIMITE, Shielded, .050 Series (PDF, English)

Application Specifications:

• AMPLIMITE .050 Series Insulation Displacement and Pr... (PDF, English)

### Instruction Sheets:

# CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version O)

- 3D Model (IGES, Version O)
- 3D Model (STEP, Version O)

## Additional Information:

## **Additional Product Images:**

- Product Photo
- Panel Cutout

# Related Products:

Tooling

List all Documents

# Product Features (Please use the Product Drawing for all design activity)

# Product Type Features: • Product Type = Connector

- Connector Type = Receptacle Number of Positions = 68
- PCB Mount Angle = Vertical
- PCB Mount Polarization = Without
- Shielded = Yes
- Shell Type = Full Metal
- Product Series = Series III
- Shell Material = Steel
- Bracket Material = Zinc
- Comment = Female screwlocks must be used to mate with cable assemblies with male jackscrew hardware.

# Mechanical Attachment: • Mating Retention = With

- Mating Alignment = Without
- Mating Retention Type = Jackscrews
- Bracket Plating = Nickel over Copper

# **Termination Related Features:**

- Termination Post Length (mm [in]) = 3.18 [0.125]
- Termination Method = Through Hole

- Body Related Features:
   Centerline (mm [in]) = 1.27 [0.050]
  - Post Plating = Tin
  - Shell Plating = Tin over Copper

## **Contact Related Features:**

- Contact Termination Type = Through Hole
- Contact Mating Area Plating Material = Gold (30), Gold Flash over Palladium Nickel
- Contact Base Material = Phosphor Bronze

- Housing Related Features:

   Housing Material = Thermoplastic
  - Housing Flammability Rating = UL 94V-0

# Configuration Related Features: • PCB Mount Retention = With

- PCB Mount Retention Type = Mounting Holes

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:
• Terminate To = Printed Circuit Board

Other:
• Brand = AMP