

### 5787394-7 Product Details



#### 5787394-7

TE Internal Number: 5787394-7



#### .050 Series Board Mount Connectors



### **Product Highlights:**

- Connector Type = Receptacle
- Number of Positions = 68
   PCB Mount Angle = Right Angle
   Through Hole Contact Termination Type

View all Features

#### **Documentation & Additional Information**

Product Drawings:

• RECEPTACLE ASSEMBLY, SHIELDED, TM RIGHT ANGLE, .050 ... (PDF, English)

### Catalog Pages/Data Sheets:

niature D Connectors - .050 Series Co... (PDF, English)

Product Specifications:

◆ Connector, AMPLIMITE, Shielded, .050 Series (PDF, English)

Application Specifications:

• AMPLIMITE .050 Series Insulation Displacement and Pr... (PDF, English)

#### Instruction Sheets:

# CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version C)

- 3D Model (IGES, Version C)
- 3D Model (STEP, Version C)

### Additional Information:

### Additional Product Images:

#### Related Products:

List all Documents

### Product Features (Please use the Product Drawing for all design activity)

## Product Type Features: • Product Type = Connector

- Connector Type = Receptacle • Number of Positions = 68
- PCB Mount Angle = Right Angle
- <u>PCB Mount Polarization</u> = Without
- Shielded = Yes
- Shell Type = Full Metal
- <u>Product Series</u> = Series III
- Shell Material = Steel
- Bracket Material = Zinc
- PCB Thickness (mm [in]) = 1.57 [0.062]

- Mechanical Attachment:
   Mating Retention = With
  - Mating Alignment = Without
  - Mating Retention Type = Latch Blocks
  - Bracket Plating = Nickel over Copper

### **Termination Related Features:**

- Termination Post Length (mm [in]) = 2.54 [0.100]
- Termination Method = Through Hole

## **Body Related Features:**

- Centerline (mm [in]) = 1.27 [0.050]
- Post Plating = Tin over Nickel
- Shell Plating = Bright Tin

- Contact Termination Type = Through Hole
- Contact Mating Area Plating Material = Gold (30), Gold Flash over Palladium Nickel
- Contact Base Material = Phosphor Bronze

- Housing Related Features:

   Housing Material = Thermoplastic
  - Housing Flammability Rating = UL 94V-0
  - Housing Color = Black

## Configuration Related Features: • PCB Mount Retention = Without

### **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:
• Terminate To = Printed Circuit Board

Other:
• Brand = AMP