


# 5520425-2 Product Details



5520425-2



# PCB Mounted Jacks - Single Port, Multi-port and Stacked



Always EU RoHS/ELV Compliant (Statement of Compliance)

## **Product Highlights:**

- Jack
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ14
- Number of Positions = 6

View all Features | Find Similar Products



#### **Documentation & Additional Information**

## **Product Drawings:**

• MODULAR JACK ASSEMBLY, TOP ENTRY, 6 POSITION, WITHOU... (PDF, English)

# **Catalog Pages/Data Sheets:**

• None Available

# **Product Specifications:**

• Modular Plugs, Thru-Hole and Surface Mount Jacks, Da... (PDF, English)

# **Application Specifications:**

• Modular Jacks (PDF, English)

### **Instruction Sheets:**

• None Available

## CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version B)
- <u>3D Model</u> (IGES, Version B)
- 3D Model (STEP, Version B)

# **Additional Information:**

Product Line Information

#### **Additional Product Images:**

- PCB Layout
- Panel Cutout

## **Related Products:**

• Tooling

List all Documents

**Product Features (Please use the Product Drawing for all design activity)** 

## **Product Type Features:**

- Product Type = Jack
- Jack Type = RJ14
- Number of Positions = 6
- PCB Mount Angle = Top Entry (Vertical)
- PCB Mount Style = Thru Hole
- <u>PCB Termination Type</u> = Solder
- Shielded = No
- Performance Category = Cat 3
- Number of Contacts Loaded = 4
- Grounding Options = Without
- Panel Stops = Without
- $\underline{\text{Keyed}} = \text{No}$
- Profile = Standard
- Color = Black
- Latch Style = Standard
- PCB Thickness (mm [in]) = 1.57 [0.062]

#### **Mechanical Attachment:**

- <u>Jack Configuration</u> = 1 x 1
- Panel Attachment = With
- Flanged = No

#### **Termination Related Features:**

- <u>Height (mm [in])</u> = 16.51 [0.650]
- Solder Tail Contact Plating = Tin over Nickel

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2007 Tyco Electronics Corporation All Rights Reserved

#### **Body Related Features:**

- Port Configuration = Single
- Inverted Jack Face = No
- $\underline{LED}$  = Without
- PCB Tail Length (mm [in]) = 3.18 [0.125]

#### **Contact Related Features:**

- Contact Mating Area Plating = Gold (50) over Nickel (50)
- Contact Material = Phosphor Bronze

#### **Housing Related Features:**

- Housing Material = Polyester (PBT)
- Housing Flammability Rating = UL 94V-0

#### **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### **Packaging Related Features:**

- Packaging Method = Tray
- Packaging Quantity = Bulk

#### Other:

• Brand = AMP