


640452-2 Product Details



640452-2



MTA, CST-100 II, MT-6 and SL Connectors and Headers



Product Highlights:

- MTA-100 Connectors
- Number of Positions = 2
- Mating Type = Header
- Wire-to-Board Application
- 2.54 mm Contact Centerline Spacing

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• MTA-100 HEADER ASSEMBLY, PLAIN, .025 SQUARE STRAIGH ... (PDF, English)

Catalog Pages/Data Sheets:

• MTA-100 AND MTA-156 CONNECTORS AND HEADERS, CST-100 ... (PDF, English)

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version Z)
- <u>3D Model</u> (IGES, Version Z)
- <u>3D Model</u> (STEP, Version Z)

Additional Information:

• Product Line Information

Related Products:

- Tooling
- Mating Products (98)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = MTA-100 Connectors
- Number of Positions = 2
- Mating Type = Header
- PCB Mount Angle = Vertical
- PCB Retention Feature = No
- Mating Polarization = Without
- Mating Connector Lock = Without
- Four Points of Contact = Without
- $\underline{Shrouded} = No$
- Mounting Ears = Without
- Post Size (mm [in]) = 0.64 [.025]

Mechanical Attachment:

• Panel Attachment = Without

Electrical Characteristics:

• Voltage Rating (VAC) = 250

Termination Related Features:

- Solder Tail Contact Plating = Tin
- Termination (Solder) Post Length (mm [in]) = 3.56 [0.140]

Body Related Features:

- Narrow = No
- Post Number(s) Omitted = None
- Solder Tail Contact Material = Copper Alloy

Contact Related Features:

- Contact Centerline Spacing (mm [in]) = 2.54 [0.100]
- <u>Contact Shape</u> = Square
- Contact Mating Area Plating = Tin
- Contact Material = Copper Alloy

Housing Related Features:

- Housing Color = White
- Housing Flammability Rating = UL 94V-0
- Housing Material = Polyester

Configuration Related Features:

• Backwall/Post Interruption(s) = Without

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Terminate To = Printed Circuit Board

Operation/Application:

• Application = Wire-to-Board

Other:

• Brand = AMP