

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

## [My Account](#)

- [Sign In](#)
- [Register](#)


## [Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [PCB Connectors](#) > [Product Feature Selector](#) > Product Details

# 87227-8 Product Details

 **Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



87227-8



### .100 inch AMPMODU Headers



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Header
- Header Type = Standard
- Number of Rows = Dual
- Number of Positions = 16
- Mating Post Length = 8.08 mm

[View all Features](#) | [Find Similar Products](#)

#### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

#### Documentation & Additional Information

**Product Drawings:**

- [ASSEMBLY, MOD II, HEADER, DOUBLE ROW, .100 X .100@22...](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version H)
- [3D Model](#) (IGES, Version H)
- [3D Model](#) (STEP, Version H)

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

[List all Documents](#)

**Product Features (Please use the Product Drawing for all design activity)****Product Type Features:**

- [Product Type](#) = Header
- [Number of Positions](#) = 16
- [Mount Angle](#) = Vertical
- [PCB Retention Feature](#) = No
- [Surface Mount Compatible](#) = No
- [Board Standoff](#) = Without
- [Mounting Ears](#) = Without
- [Mating Connector Lock](#) = Without
- Post Size (mm [in]) = 0.64 [.025]

**Mechanical Attachment:**

- Mating Post Length (mm [in]) = 8.08 [0.318]
- [Panel Attachment](#) = Without

**Electrical Characteristics:**

- Current Rating (Amps.) = 3
- Insulation Resistance (M $\bullet$ ) = 5,000
- Dielectric Withstanding Voltage (V) = 750

**Termination Related Features:**

- [Termination \(Solder\) Post Length \(mm \[in\]\)](#) = 3.18 [0.125]
- Solder Tail Contact Plating = Gold Flash over Nickel

**Body Related Features:**

- Header Type = Standard
- [Number of Rows](#) = Dual
- [Centerline, Matrix \(mm \[in\]\)](#) = 2.54 x 2.54 [.100 x .100]
- [Selectively Loaded](#) = No
- [Mount Type](#) = PC Board

**Contact Related Features:**

- [Contact Mating Area Plating Material](#) = Gold (15)
- Contact Shape = Square
- Contact Material = Phosphor Bronze
- Approved Standards = UL E28476, CSA LR7189

**Housing Related Features:**

- Housing Material = Thermoplastic
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C
- RoHS/ELV Compliance History = Always was RoHS compliant

**Conditions for Usage:**

- [High Temperature Housing](#) = No
- Operating Temperature (°C) = -65 – +105

**Operation/Application:**

- [High Speed Serial Data Connector](#) = No

**Other:**

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved