


# 925486-1 Product Details



925486-1



# **Eurocard Type C**



# **Product Highlights:**

- Type C Housings
- Receptacle
- Number of Positions = 96
- Terminate To Wire
- No PCB Retention Feature

View all Features | Find Similar Products



# **Documentation & Additional Information**

# **Product Drawings:**

• 96 POS. AMPMODU IV CRIMP-SNAP-IN HOUSING (PDF, English)

# Catalog Pages/Data Sheets:

• EUROCARD CONNECTORS PER DIN 41612 AND IEC 603-2 (PDF, English)

- Interconnection System, AMPMODU Mod IV 1/2 (PDF, English)
- Receptacle, Tandem Spring Contact (PDF, English)

# **Application Specifications:**

• None Available

# **Instruction Sheets:**

• None Available

# CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version M3)
- <u>3D Model</u> (IGES, Version M3)
- 3D Model (STEP, Version M3)

# **Additional Information:**

• Product Line Information

# **Related Products:**

- Tooling
- Mating Products (22)

List all Documents

# **Product Features** (Please use the Product Drawing for all design activity)

# **Product Type Features:**

- <u>Product Type</u> = Type C Housings
- Gender = Receptacle
- Number of Positions = 96
- PCB Retention Feature = No
- Wire Termination Type = Crimp
- $\underline{Size} = Standard$
- Make First / Break Last = No
- Mounting Ears = With
- Toolless (Flat Rock) = No
- Color = Gray
- Comment = Reference crimp-snap-in contact series 166500 and 166722.

# **Mechanical Attachment:**

• Contact Retention in Housing = Crimp Snap-In

# **Housing Related Features:**

- Housing Material = Polycarbonate
- Housing Flammability Rating = UL 94V-1

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- Flux-Tight Coating = Without
- RoHS/ELV Compliance History = Always was RoHS compliant

# **Conditions for Usage:**

- <u>Terminate To</u> = Wire
- <u>High Temperature Housing</u> = No

# Other:

• Brand = AMP