Products

Documentation

Resources

My Account

Customer Support

Home > Products > Eurocard Connectors > Product Feature Selector > Product Details

5535032-4 Product Details

Have a Question?

Chat with a Product Information Specialist

Quick Links





Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Preloaded
- Contact Gender = Receptacle
- Housing Gender = Plug
- Type = Type C
- 2.54 mm Centerline

View all Features



Product Feature Selector Contact Us About This Product

Check Pricing & Availability Search for Tooling



TE Internal Number: 5535032-4











Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Additional Information:

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- PCB Mount Retention = With
- PCB Mount Angle = Vertical
- PCB Thickness (Minimum) (mm [in]) = 1.57 [0.062]
- Post Type = Compliant Post
- Size = Standard
- Make First / Break Last = No
- Bus Type = FUTUREBUS, MULTIBUS (II), NUBUS, VMEbus, VXIBus
- DIN Level = II
- Mounting Ears = With
- Toolless (Flat Rock) = Yes

Termination Related Features:

- Termination Post Length (mm [in]) = 4.83 [0.190]
- Solder Tail Contact Plating = Gold Flash over Nickel

Body Related Features:

- Type = Type C
- Centerline (mm [in]) = 2.54 [0.100]
- Number of Rows = 3
- Number of Positions = 96
- Rows Loaded = A, B, C
- PCB Mount Retention Type = ACTION PIN (Compliant) Posts
- Contact Cross Section (mm [in]) = 0.30 x 0.61 [.012 x .024]

Contact Related Features:

- Preloaded = Yes
- Contact Gender = Receptacle
- Contact Base Material = Phosphor Bronze

Housing Related Features:

- Housing Gender = Plug
- Housing Material = Polyester
- UL Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- <u>Flux-Tight Coating</u> = Without
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Applies To = Printed Circuit Board
- High Temperature Housing = No

Other:

Brand = AMP



Investors

Corporate Information **Ouick Links**

Who We Are Check Distributor Inventory

Find Documents & Drawings News Room Supplier Portal Product Compliance Support Center

Cross Reference

Careers Site Map Customer Support

Email or Chat with Us Find a Phone Number Search Knowledge Base Manage Your Account

Sign up for our eNewsletter

Enter your email address



Follow us on:

Provide Website Feedback

