Our commitment. Your advantage

Products

Documentation

Resources My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Eurocard Connectors</u> > <u>Product Feature Selector</u> > Product Details

5650934 - 5 Product Details



5650934 - 5

✓ Active

Eurocard Type R

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Plug
- Number of Positions = 64
- ? PCB Mount Angle = Vertical
- ? No PCB Retention Feature
- ? Post Type = Solder Post

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>



Quick Links

Check Pricing &
Availability
Search for Tooling
View Mating
Products (11)
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

ASSEMBLY, PIN, EUROCARD, TYPE R, A and C, 64/96 POSI... (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

None Available

Application Specifications:

2 Eurocard Connectors Types B,C,M,Q,R, & Enchanced Typ... (PDF English)

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information

- ? 2D Drawing (DXF, Version O)
- ? 3D Model (IGES, Version O)
- ? 3D Model (STEP, Version O)

Additional Information:

? Product Line Information

Related Products:

- ? Tooling
- ? Mating Products (11)

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Plug
- ? Number of Positions = 64
- ? PCB Mount Angle = Vertical
- ? PCB Retention Feature = No
- ? Post Type = Solder Post
- ? <u>Mating Polarization</u> = Without
- ? Guides = Without
- ? Make First / Break Last = No
- ? DIN Level = II
- ? Color = Gray

Termination Related Features:

- 7 Termination (Solder) Post Length (mm [in]) 4.57 [0.180]
- ? Solder Tail Contact Plating = Tin

Body Related Features:

- Rows Loaded = A, C
- ? Contact Cross Section (mm [in]) = 0.64 [.025] Sq.

Contact Related Features:

- ? Contact Material = Copper Alloy
- Contact Mating Area Plating Material = DIN 41612 Class 2

Housing Related Features:

- ? Housing Material = Polymer
- Housing Flammability Rating = UL 94V -0

Industry Standards:

- ROHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? Flux Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support