Our commitment. Your advantage.

•

Products

Desumentation

Resources My Account

Customer Support

Home > Products > By Type > Eurocard Connectors > Product Feature Selector > Product Details

5650945 - 5 Product Details



5650945 - 5

✓ Active

Eurocard Type C

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Type C Connectors
- Plug
- ? Number of Positions = 64
- ? Rows Loaded = A, C
- ? Terminate To Printed Circuit Board

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>



Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

ASSEMBLY, PIN, EUROCARD, TYPE C, A and C, 64/96 POSI...
 (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

Eurocard Connectors Types B,C,M,Q,R, & Enchanced Typ... (PDF English)

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

? Product Line Information

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Type C Connectors
- ? Gender = Plug
- ? Number of Positions = 64
- ? PCB Retention Feature = No
- ? PCB Mount Angle = Right Angle
- ? Post Type = Solder Post
- ? Size = Standard
- ? Make First / Break Last = No
- ? DIN Level = II
- ? Mounting Ears = Without
- ? Guides = Without
- ? Toolless (Flat Rock) = No
- ? Color = Gray

Termination Related Features:

7 Termination (Solder) Post Length (mm [in]) = 2.65 [0.104]

Body Related Features:

- Rows Loaded = A, C
- ? Contact Cross Section (mm [in]) = 0.64 [.025] Sq.

Contact Related Features:

? Contact Material = Brass

Housing Related Features:

- ? Housing Material = Polymer
- ? Housing Flammability Rating = UL 94V -0

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? Flux Tight Coating = Without
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Terminate To = Printed Circuit Board
- ? High Temperature Housing = No

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support