• Check Distributor Inventory

o Find Authorized Distributors



- о <u>Sign In</u>
- <u>Register</u>

# . Customer Support

- o Support
- <u>RoHS Support Center</u>
- o Glossary of Terms
- o <u>eBulletin Newsletter</u>

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Product Feature Selector</u> > Product Details

# 292161-3 Product Details



**Documentation & Additional Information** 

## **Product Drawings:**

• POST HEADER ASS'Y VERTICAL TYPE (AMP CT CONNECTOR 2m... (PDF, English)

#### Catalog Pages/Data Sheets:

• REPRESENTATIVE TERMINALS AND CONNECTORS (PDF, English)

## Product Specifications:

None Available

## Application Specifications:

None Available

#### Instruction Sheets:

• None Available

## CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version O)
- <u>3D Model</u> (IGES, Version O)
- <u>3D Model</u> (STEP, Version O)

#### **Additional Information:**

Product Line Information

## **Related Products:**

- Tooling
  - Mating Products (3)

## List all Documents

## Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- <u>Product Type</u> = Connector
- <u>Connector Type</u> = MT (Mass Termination)
- Mating Type = Header
- <u>Number of Positions</u> = 3
- <u>PCB Mount Style</u> = Thru Hole
- <u>PCB Mount Angle</u> = Vertical
- <u>PCB Polarization</u> = No
- <u>PCB Retention Feature</u> = Yes

## **Mechanical Attachment:**

• <u>Panel Attachment</u> = Without

## **Termination Related Features:**

• Solder Tail Contact Plating = Tin

#### Body Related Features:

- <u>Number of Rows</u> = 1
- <u>Header Body Style</u> = Standard
- <u>PCB Retention Method</u> = Retention Solder Tails
- Centerline (mm [in]) = 2.00 [0.079]

## Contact Related Features:

- Contact Material = Brass
- Contact Mating Area Plating Material = Tin

## Housing Related Features:

- Housing Material = Nylon
- Housing Color = Natural
- Housing Flammability Rating = UL 94V-0

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

• <u>Terminate To</u> = Printed Circuit Board

## Other:

• Brand = AMP

Provide Website Feedback | Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved