- o Check Distributor Inventory
- Find Authorized Distributors

. My Account


- o Sign In
- o Register

. Customer Support

- o Support
- o RoHS Support Center
- o Glossary of Terms
- o eBulletin Newsletter

Home > Products > By Type > PCB Connectors - Wire to Board - Power > Product Feature Selector > Product Details

3-640440-2 Product Details



Documentation & Additional Information

Quick Links

- Check
 Pricing &
 Availability
- Search for Tooling
- <u>View Mating</u> <u>Products (54)</u>
- Product
 Feature
 Selector
- Contact Us
 About This
 Product

Product Drawings:

• MTA 100 CONNECTOR ASSEMBLY, 22 AWG, STANDARD (PDF, English)

Catalog Pages/Data Sheets:

• MTA-100 AND MTA-156 CONNECTORS AND HEADERS, CST-100 ... (PDF, English)

Product Specifications:

• None Available

Application Specifications:

• MTA 100 Connector Assemblies (English And Spanish) (PDF, English)

Instruction Sheets:

• None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version M)
- 3D Model (IGES, Version M)
- 3D Model (STEP, Version M)

Additional Information:

• Product Line Information

Additional Product Images:

• Product Photo

Related Products:

- Tooling
- Mating Products (54)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = MTA-100 Connectors
- Number of Positions = 2
- Mating Type = Receptacle
- Connector Type = Closed End
- Wire Termination Type = IDC Standard
- Wire Size (mm² [AWG]) = 0.3-0.4² [22]
- Mating Polarization = Without
- Mating Connector Lock = With
- Four Points of Contact = Without
- $\underline{Shrouded} = No$
- Mounting Ears = Without

Mechanical Attachment:

• Panel Attachment = Without

Electrical Characteristics:

• Voltage Rating (VAC) = 250

Termination Related Features:

• Solder Tail Contact Plating = Tin

Body Related Features:

- $\underline{Narrow} = No$
- Post Number(s) Omitted = None
- Cable Exit Angle = 90°

Contact Related Features:

- Contact Centerline Spacing (mm [in]) = 2.54 [0.100]
- Contact Mating Area Plating Material = Tin
- Contact Material = Copper Alloy

Housing Related Features:

- Housing Color = Red
- Housing Flammability Rating = UL 94V-2
- Housing Material = Nylon

Industry Standards:

- $\bullet \ \ \, \underline{RoHS/ELV\ Compliance} = RoHS\ compliant,\ ELV\ compliant \\$
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• $\underline{\text{Terminate To}} = \text{Wire}$

Operation/Application:

• Application = Wire-to-Board, Wire-to-Wire

Packaging Related Features:

• Packaging Method = Loose Piece

Other:

• Brand = AMP

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2008 Tyco Electronics Corporation All Rights Reserved