


5-102570-6 Product Details



5-102570-6



.100 inch AMPMODU Headers



Product Highlights:

- Header
- Header Type = Shrouded
- Number of Rows = Dual
- Number of Positions = 16
- Mating Post Length = 8.08 mm

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• HDR ASSY, MOD II, SHROUDED, .100X.100 C/L 4 SIDES, ... (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Header
- Number of Positions = 16
- Shrouded End Dimension (mm [in]) = 3.81 [0.150]
- Mount Angle = Right Angle
- PCB Retention Feature = No
- Surface Mount Compatible = No
- Board Standoff = With
- Mounting Ears = Without
- Mating Connector Lock = With
- Mating Connector Lock Type = Detent Windows
- Housing Style = 4-Sided
- Post Size (mm [in]) = 0.64 [.025]
- Profile = Standard

Mechanical Attachment:

- Mating Post Length (mm [in]) = 8.08 [0.318]
- Panel Attachment = Without

Electrical Characteristics:

- Current Rating (Amps.) = 3
- Insulation Resistance (M•) = 5,000
- Dielectric Withstanding Voltage (V) = 750

Termination Related Features:

- Termination (Solder) Post Length (mm [in]) = 3.43 [0.135]
- Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- <u>Header Type</u> = Shrouded
- Number of Rows = Dual
- Centerline, Matrix (mm [in]) = 2.54 x 2.54 [.100 x .100]
- <u>Selectively Loaded</u> = No
- Mount Type = PC Board

Contact Related Features:

- Contact Mating Area Plating = Gold (15)
- Contact Shape = Square
- Contact Material = Phosphor Bronze
- Approved Standards = UL E28476, CSA LR7189

Housing Related Features:

- Housing Material = Thermoplastic
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- High Temperature Housing = No
- Operating Temperature (°C) = -55 +125

Operation/Application:

• High Speed Serial Data Connector = No

Other:

• Brand = Tyco Electronics