

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

## [My Account](#)

- [Sign In](#)
- [Register](#)


## [Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [PCB Connectors - Wire to Board - Power](#) > [Product Feature Selector](#) > Product Details

# 770602-4 Product Details


Live Product Chat US Only  
 8:30am - 5pm ET, Mon - Fri



**770602-4**

 [Active](#)

 [View 3D PDF](#)

### MTA, CST-100 II, MT-6 and SL Connectors and Headers



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- CST-100 Housings
- Number of Positions = 4
- Mating Type = Receptacle
- Wire-to-Board Application
- 2.54 mm Contact Centerline Spacing

[View all Features](#) | [Find Similar Products](#)

#### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

#### Documentation & Additional Information

**Product Drawings:**

- [rcpt cst-100 loose piece](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- [CST-100 Connectors for Crimp Snap Terminals](#) (PDF, English)

**Instruction Sheets:**

- [CST-100 Receptacles Visual Training Aid \(Contact Hel...](#) (PDF, English)
- [CST-100 Receptacles Visual Training Aid \(Contact Ins...](#) (PDF, English)
- [CST-100 Receptacles Visual Training Aid \(Reel Orient...](#) (PDF, English)
- [CST-100 Receptacles Visual Training Aid \(Lance Position\)](#) (PDF, English)

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version F)
- [3D Model](#) (IGES, Version F)
- [3D Model](#) (STEP, Version F)

**Additional Information:**

- [Product Line Information](#)

**Additional Product Images:**

- [Product Photo](#)

**Related Products:**

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

**Product Type Features:**

- Product Type = CST-100 Housings
- [Number of Positions](#) = 4
- [Mating Type](#) = Receptacle
- [Wire Termination Type](#) = Crimp
- [Mating Polarization](#) = Without
- [Mating Connector Lock](#) = With
- [Four Points of Contact](#) = Without
- [Shrouded](#) = No
- [Mounting Ears](#) = Without
- Comment = Accepts Contact Part No. 770601-1.

**Mechanical Attachment:**

- [Panel Attachment](#) = Without

**Body Related Features:**

- Cable Exit Angle = 180°

**Contact Related Features:**

- [Contact Centerline Spacing \(mm \[in\]\)](#) = 2.54 [0.100]

**Housing Related Features:**

- Housing Color = White
- Housing Flammability Rating = UL 94V-0
- Housing Material = Nylon

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

**Operation/Application:**

- [Application](#) = Wire-to-Board

**Packaging Related Features:**

- Packaging Quantity = 500

**Other:**

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved