- o Check Distributor Inventory
- Find Authorized Distributors

# . My Account

- o Sign In
- o Register


# . Customer Support

- o Support
- o RoHS Support Center
- o Glossary of Terms
- o eBulletin Newsletter

Home > Products > By Type > PCB Connectors - Wire to Board - Power > Product Feature Selector > Product Details

# 770602-9 Product Details

Live Product Chat US Only



770602-9



MTA, CST-100 II, MT-6 and SL Connectors and Headers



## **Product Highlights:**

- CST-100 Housings
- Number of Positions = 9
- Mating Type = Receptacle
- Wire-to-Board Application
- 2.54 mm Contact Centerline Spacing

View all Features | Find Similar Products

**Documentation & Additional Information** 

Quick Links

- Check
  Pricing &
  Availability
- Search for Tooling
- Product
  Feature
  Selector
- Contact Us
  About This
  Product

## **Product Drawings:**

• rcpt cst-100 loose piece (PDF, English)

## Catalog Pages/Data Sheets:

None Available

## **Product Specifications:**

• None Available

## **Application Specifications:**

• CST-100 Connectors for Crimp Snap Terminals (PDF, English)

#### **Instruction Sheets:**

- CST-100 Receptacles Visual Training Aid (Contact Hel... (PDF, English)
- CST-100 Receptacles Visual Training Aid (Contact Ins... (PDF, English)
- CST-100 Receptacles Visual Training Aid (Reel Orient... (PDF, English)
- CST-100 Receptacles Visual Training Aid (Lance Position) (PDF, English)

## CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version F)
- 3D Model (IGES, Version F)
- <u>3D Model</u> (STEP, Version F)

#### **Additional Information:**

• Product Line Information

## **Additional Product Images:**

• Product Photo

#### **Related Products:**

• Tooling

## List all Documents

## Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- Product Type = CST-100 Housings
- Number of Positions = 9
- Mating Type = Receptacle
- <u>Wire Termination Type</u> = Crimp
- Mating Polarization = Without
- Mating Connector Lock = With
- Four Points of Contact = Without
- $\underline{Shrouded} = No$
- Mounting Ears = Without

#### **Mechanical Attachment:**

• Panel Attachment = Without

## **Body Related Features:**

• Cable Exit Angle = 180°

#### **Contact Related Features:**

• Contact Centerline Spacing (mm [in]) = 2.54 [0.100]

## **Housing Related Features:**

- Housing Color = White
- Housing Flammability Rating = UL 94V-0
- Housing Material = Nylon

## ${\bf Industry\ Standards:}$

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

## Operation/Application:

• Application = Wire-to-Board

## Other:

• Brand = AMP

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2008 Tyco Electronics Corporation All Rights Reserved