

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

[My Account](#)

- [Sign In](#)
- [Register](#)


[Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [PCB Connectors - Wire to Board - Power](#) > [Product Feature Selector](#) > Product Details

770849-5 Product Details

 **Live Product Chat** US Only
8:30am - 5pm ET, Mon - Fri



770849-5



[Active](#)

MTA, CST-100 II, MT-6 and SL Connectors and Headers



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- SL-156 Housings
- Number of Positions = 5
- Mating Type = Receptacle
- Wire-to-Board Application
- 3.96 mm Contact Centerline Spacing

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [View Mating Products \(84\)](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [HOUSING WITH LOCKING](#) (PDF, English)

Catalog Pages/Data Sheets:

- [MTA-100 AND MTA-156 CONNECTORS AND HEADERS, CST-100 ...](#) (PDF, English)

Product Specifications:

- [Connector, SL 156](#) (PDF, English)
- [Connector, Hooded SL 156](#) (PDF, English)
- [Connector, Hooded SL 156, Tin](#) (PDF, English)

Application Specifications:

- [SL 156 Contacts and Housings](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version N)
- [3D Model](#) (IGES, Version N)
- [3D Model](#) (STEP, Version N)

Additional Information:

- [Product Information](#)
- [Product Line Information](#)

Additional Product Images:

- [Product Photo](#)

Related Products:

- [Tooling](#)
- [Mating Products \(84\)](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- [Product Type](#) = SL-156 Housings
- [Number of Positions](#) = 5
- [Mating Type](#) = Receptacle
- [Wire Termination Type](#) = Crimp
- [Mating Polarization](#) = With
- [Mating Connector Lock](#) = With
- [Four Points of Contact](#) = Without
- [Shrouded](#) = No
- [Mounting Ears](#) = Without
- Mating Connector Lock Type = Locking Ramp
- Mating Polarization Method = Polarizing Tab
- Comment = Recommended contact: Part No. 640252-1,-2 and Part No. 770476-1,-2.

Mechanical Attachment:

- [Panel Attachment](#) = Without
- Wire Insulation Diameter Size = Standard

Body Related Features:

- Cable Exit Angle = 180°

Contact Related Features:

- [Contact Centerline Spacing \(mm \[in\]\)](#) = 3.96 [0.156]

Housing Related Features:

- Housing Color = White
- Housing Flammability Rating = UL 94V-0
- Housing Material = Nylon

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

- [Application](#) = Wire-to-Board

Packaging Related Features:

- Packaging Quantity = 500

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved

■