


211149-1 Product Details



211149-1

TE Internal Number: 211149-1







5mm (.197") Centerline, 600 V, 14 A max. (Metrimate)

Product Highlights:

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Housing
- Housing
 Drawer Connector Configuration
- Drawer Style = Standard
- 25 Positions

View all Features

Documentation & Additional Information

Product Drawings:

• pin housing, 25 posn metrimate (PDF, English)

Catalog Pages/Data Sheets:

METRIMATE PIN SOCKET CATALOG (PDF, English)

Product Specifications:

· None Available

Application Specifications:

- HDD (High Durability Drawer) Connectors (PDF, English)
- APPLICATION SPECIFICATION, METRIMATE DRAWER CONNECTORS (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version Z)

- <u>3D Model</u> (IGES, Version Z)
- <u>3D Model</u> (STEP, Version Z)

Additional Information:

Related Products:

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Product Type</u> = Housing
- Connector Type = Housing
- Gender = Receptacle • <u>Keyed</u> = No
- Mount = Panel
- <u>Mounting Ears</u> = Without
- Mating Connector Lock = Without
- PCB Mount Retention = Without

Electrical Characteristics:

Voltage (VAC) = 600

Body Related Features:

- Connector Configuration = Drawer
- <u>Drawer Style</u> = Standard
- Number of Positions = 25
- Coaxial Socket = Without
- <u>Centerline (mm [in])</u> = 5.08 [0.200]
- 8/32 Insert = No

Housing Related Features:

- Housing Material = Polyester
- Housing Color = Black
- UL Flammability Rating = UL 94V-0

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

- Brand = AMP
- Comment = Positions 1 & 25 should not be used with ground