

3-350819-2 Product Details



TE Internal Number: 3-350819-2





Ultra-Fast Receptacles & Tabs

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Terminal Type = ReceptacleProprietary Name = Ultra-Fast
- Receptacle Style = Straight
- Mating Area Interface Dimensions = 6.35 x 0.81
- Brass Material

View all Features







Documentation & Additional Information

Product Drawings:

RECEPTACLE ASSY, ULTRA-FAST, .250 SERIES, 16-14 AWG (PDF, English)

Catalog Pages/Data Sheets:

- Automachine and General Products (PDF, English)
- <u>Ultra-Fast and Ultra Fast Plus</u> (PDF, English)

Product Specifications:

<u>Ultra-Fast Fully Insulated FASTON Receptacle Terminals</u> (PDF, English)

Application Specifications:

Instruction Sheets:

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version R)
- <u>3D Model</u> (IGES, Version R)
- 3D Model (STEP, Version R)

Additional Information:

Related Products:

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Terminal Type = Receptacle
- <u>Proprietary Name</u> = Ultra-Fast
- Receptacle Style = Straight
- Mating Area Interface Dimensions (mm [in]) = 6.35 x 0.81 [.250 x .032]
- Material = Brass
- Insulation Diameter (mm [in]) = 4.06 [.160] Max.
- <u>Insulation Support</u> = Non-Insulation Support
- Industry Application = Standard
- Finish = Tin

Body Related Features:

- Wire Range (mm [AWG]) = 1.25-2.00² [16-14]
- Fully Insulated = Yes

Housing Related Features:

UL Flammability Rating = UL 94V-2

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

Packaging Method = Strip

Other:

Brand = AMP

© 2010 Tyco Electronics All Rights Reserved Privacy Policy