
X

2-520183-2 Product Details



2-520183-2



Ultra-Fast Receptacles & Tabs



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Receptacle
- Proprietary Name = Ultra-Fast
- Receptacle Style = Straight
- Tab Fit = $6.35 \times 0.81 \text{ mm}$
- Brass Material

View all Features | Find Similar Products



Documentation & Additional Information

Product Drawings:

• RECEPTACLE ASSY, ULTRA-FAST, (PDF, English)

Catalog Pages/Data Sheets:

- Automachine and General Products (PDF, English)
- FASTON TERMINALS (INSULATED & UNINSULATED) (PDF, English)

Product Specifications:

• <u>Ultra-Fast Fully Insulated FASTON Receptacle Terminals</u> (PDF, English)

Application Specifications:

• Ultra-Fast Series 110, 125, 187, 205, and 250 Fully-... (PDF, English)

Instruction Sheets:

• None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version P)
- 3D Model (IGES, Version P)
- 3D Model (STEP, Version P)

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Receptacle
- Proprietary Name = Ultra-Fast
- Receptacle Style = Straight
- <u>Tab Fit (mm [in])</u> = 6.35 x 0.81 [.250 x .032]
- Material = Brass
- Insulation Diameter (mm [in]) = 3.43 [.135] Max.
- <u>Insulation Support</u> = Non-Insulation Support
- Industry Application = Standard
- $\bullet \quad Finish = Tin$

Body Related Features:

- Wire Range (mm [AWG]) = 0.30-0.90² [22-18]
- \bullet Fully Insulated = Yes
- Flammability Rating = UL 94V-2

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

• Packaging Method = Strip

Other:

• Brand = AMP