


2-521055-2 Product Details



<u>Active</u>

Niew 3D PDF

Ultra-Fast Receptacles & Tabs

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Product Highlights:
- Terminal Type = Tab
 Proprietary Name = Ultra-Fast Plus
 Mating Area Interface Dimensions = 6.35 x 0.81
- mm Brass Material
- Insulation Diameter = 1.52-3.42 [.060-.135] mm [in]

View all Features

Product Drawings: • <u>TAB ASSEMBLY,ULTRA-FAST,</u> (PDF, English)		Additional Information: Product Line Information
atalog Pages/Data Sheets: • <u>Ultra-Fast and Ultra Fast Plus</u> (PDF, English)		Related Products: • <u>Tooling</u>
Product Specifications:None Available		
Application Specifications: None Available 		
Instruction Sheets: None Available 		
 AD Files: (CAD Format & Compression Information) 2D Drawing (DXF, Version F) 3D Model (IGES, Version F) 		
• <u>3D Model</u> (STEP, Version F)		
	List all Documents	

Product Features (Please use the Product Drawing for all design activity) Product Type Features: Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant • Terminal Type = Tab • <u>Proprietary Name</u> = Ultra-Fast Plus • Lead Free Solder Processes = Not relevant for lead free ٠ Mating Area Interface Dimensions (mm [in]) = 6.35 x 0.81 process • RoHS/ELV Compliance History = Always was RoHS compliant [.250 x .032] • Material = Brass • <u>Insulation Diameter (mm [in])</u> = 1.52-3.42 [.060-.135] Packaging Related Features: <u>Packaging Method</u> = Strip • <u>Insulation Support</u> = Insulation Support • Industry Application = Standard • Brand = AMP • Finish = Tin • Wire/Cable Type = Regular Wire • Mount Angle = Straight **Body Related Features:** • <u>Wire Range (mm [AWG])</u> = 0.30-0.90² [22-18] • Tab Type = Wire Crimp • Fully Insulated = Fully Insulated