


324061 Product Details



TE Internal Number: 324061







Ring and Spade Tongue Terminals

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Terminal Shape = Ring Tongue
- Receptacle Style = Straight Body Style = SOLISTRAND
- Barrel Type = Closed Barrel
- Wire/Cable Type = Regular Wire

View all Features

Documentation & Additional Information

Product Drawings:

 TERMINAL , RING TONGUE, SOLISTRAND (PDF, English)

Catalog Pages/Data Sheets:

- AEROSPACE & DEFENSE (PDF, English)
- SOLISTRAND BUDGET AND DIAMOND GRIP UNINSULATED TERMI... (PDF, English)
- STRATO-THERM TERMINALS& SPLICES FOR HIGH TEMP APPL (PDF, English)

Product Specifications:

· None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information) ■ 2D Drawing (DXF, Version S)

- <u>3D Model</u> (IGES, Version S)
- 3D Model (STEP, Version S)

Additional Information:

Related Products:

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Terminal Shape</u> = Ring Tongue
- Receptacle Style = Straight
- <u>Body Style</u> = SOLISTRAND • <u>Barrel Type</u> = Closed Barrel
- <u>Wire/Cable Type</u> = Regular Wire
- <u>Insulation</u> = No
- <u>Insulation Support</u> = Non-Insulation Support
- <u>Stud Diameter (mm [in])</u> = 4.34 [0.171]
- Stud Size = 8 [M4]
- Shape = RING-049
- Heavy Duty = No
- Material = Copper Finish = Tin

Termination Related Features: • Wire/Cable Size (CMA) = 13,100 - 20,800

Body Related Features:

- Wire Range (mm [AWG]) = 8.00² [8]
- Barrel I.D. Min. (mm [in]) = 4.37 [0.172]
- Stock Thickness (mm [in]) = 1.22 [0.048]

Contact Related Features:

Class = 2

Industry Standards:

- Government/Industry Qualification = Yes
- Government/Industry Part Number = MS20659-140
- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• High Temperature Rating (°C [°F]) = 170 [338]

Packaging Related Features:

Packaging Method = Loose Piece

Other:

• Brand = AMP