


34138 Product Details



34138

TE Internal Number: 34138

 [Active](#)

 [View 3D PDF](#)

Splices - Closed Barrel

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Splice
- Not Sealed
- Splice Type = Parallel
- Body Style = SOLISTRAND
- Uninsulated

[View all Features](#)

Documentation & Additional Information

Product Drawings:

- [SPLICE, PARALLEL, SOLISTRAND](#) (PDF, English)

Catalog Pages/Data Sheets:

- [SOLISTRAND BUDGET AND DIAMOND GRIP UNINSULATED TERMI...](#) (PDF, English)
- [ENERGY READY REFERENCE 2000](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version Y)
- [3D Model](#) (IGES, Version Y)
- [3D Model](#) (STEP, Version Y)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Splice
- [Sealed](#) = No
- [Splice Type](#) = Parallel
- [Body Style](#) = SOLISTRAND
- [Insulation](#) = No
- [Insulation Support](#) = Non-Insulation Support
- [Material](#) = Copper
- [Finish](#) = Tin
- [Color](#) = None

Mechanical Attachment:

- [Inside Diameter \(mm \[in\]\)](#) = 3.28 [0.129]

Termination Related Features:

- [Wire/Cable Size \(CMA\)](#) = 5,180 - 13,100

Body Related Features:

- [Wire Range \(mm \[AWG\]\)](#) = 3.00-6.00² [12-10]
- [Stock Thickness \(mm \[in\]\)](#) = 1.07 [0.042]
- [Outside Diameter \(mm \[in\]\)](#) = 5.74 [0.226]

Industry Standards:

- [Government/Industry Qualification](#) = No
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Packaging Related Features:

- [Packaging Method](#) = Loose Piece

Other:

- [Brand](#) = AMP