

770986-3

TE Internal Number: 770986-3

Active

.163" Centerline, 600 V, 9.5 A max.

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

- Contact
- Mini-Universal MATE-N-LOK
- Socket
- Packaging Method = Loose Piece
- Wire Range = 0.12-0.40² [26-22] mm [AWG]

View all Features

Documentation & Additional Information	
 Product Drawings: <u>SOCKET, LOOSE PIECE, MINI UNIVERSAL MATE-N-LOK(TM)</u> (PDF, English) Catalog Pages/Data Sheets: <u>MINIATURE CIRCULAR PLASTIC CONNECTOR (CPC)</u> (PDF, English) <u>CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND</u> <u>POWER</u> (PDF, English) <u>SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG</u> (PDF, English) Product Specifications: 	Additional Information: • Product Line Information Related Products: • Tooling • Housings (265)
 None Available Application Specifications: Mini-Universal MATE-N-LOK Splash-Proof Sealed Connectors (PDF, English) Mini-Universal MATE-N-LOK Connectors (PDF, English) 	
Instruction Sheets: • None Available CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version H) • 3D Model (IGES, Version H) • 3D Model (STEP, Version H) List all Documents	

 Product Type Features: Product Type = Contact Compositor Line Mini Universal MATE N LOK 	Contact Related Features: • Contact Base Material = Brass
 Connector Line = Mini-Universal MATE-N-LOK Gender = Socket Wire Insulation Diameter (mm [in]) = 1.20 – 1.75 [0.047 – 0.069] 	 CompactPCI = No Industry Standards: <u>RoHS/ELV Compliance</u> = Not ELV/RoHS compliant
 Electrical Characteristics: Voltage (VAC) = 600 Current Rating (Amps.) = 9.5 	 <u>Lead Free Solder Processes</u> = Not relevant for lead free process Packaging Related Features:
Termination Related Features:Solder Tail Contact Plating = Duplex	 Packaging Method = Loose Piece Other:
 Body Related Features: Wire Range (mm [AWG]) = 0.12-0.40² [26-22] Contact Diameter (mm [in]) = 0.99 [0.039] Stock Thickness (mm [in]) = 0.20 [0.008] 	• Brand = AMP