

3400N Series cont. Tubeaxial

92x92x25mm



- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity, blocking and overloading; partially impedance protected.
- Mounting from either face using four 4.3 mm holes.
- Fan of fiberglass reinforced plastic. PBTP housing, PA impeller.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Electrical connection via 2 leads AWG 24, TR 64. Stripped and tinned ends.
- UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	Curve	CFM @ 0	VDC	Volt. Range	Power (W)	dBA	Max Amb. Temp C	Bearing Type	Features	Wgt. (lbs)
3414NGL	1	35.9	24	18 to 28	1.4	23	70	Sintec	Leads	0.22
3414NL	1	35.9	24	18 to 28	1.4	23	70	Ball	Leads	0.22
3414NM	2	42.4	24	18 to 28	1.8	28	70	Ball	Leads	0.22
3414NGM	2	42.4	24	18 to 28	1.8	28	70	Sintec	Leads	0.22
3414N	3	49.4	24	18 to 28	2.3	32	70	Ball	Leads	0.22
3414NG	3	49.4	24	18 to 28	2.3	32	70	Sintec	Leads	0.22
3414NGH	4	55.3	24	18 to 26	3.0	36	70	Sintec	Leads	0.22
3414NH	4	55.3	24	18 to 26	3.0	36	70	Ball	Leads	0.22
3414NGHH-389	5	60.0	24	18 to 28	3.2	39	70	Sintec	Leads	0.22
3414NHH-386	5	60.0	24	18 to 28	3.2	39	70	Ball	Leads	0.22

