

[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [Single-ended I/O Fan-out and Zero Delay Buffers](#) > [9112-22](#) > [9112M-22](#)

[Add to myIDT \[?\]](#)

You may also like...


9112M-22

Category: [Single-ended I/O Fan-out and Zero Delay Buffers](#)

Generic Part: [9112-22](#)

Market Group: PC CLOCK

Description: PC BUFFER
 The ICS9112-22 is a high performance, low skew, low jitter clock driver. It is designed to distribute high speed clocks in PC systems operating at speeds from 25 to 133 MHz.



Parameters

Package	SOIC 8 (DC8)
Voltage	3.3 V
Package	SOIC 8
Speed	NA
Temperature	C
Status	Active
Sample	Yes
Minimum Order Quantity	194
Factory Order Increment	97

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SOIC(SOP) 150 ML, 8 LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	240°C
Rebake Conditions	NA
Length	4.9
Mark	S
Width	3.9
Pitch	1.27
Thickness	1.5
Status	Active