

This document was generated on 06/02/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | <u>0002082003</u> | | al A |
|---|-------------------------------------|---|--|
| Status: | Active | | |
| Overview: Description: | <u>mlx</u> MLX Crimp Terminal 42 | 023, 14-20 AWG, Reel Tin (Sn) | |
| Documents: | | | |
| 3D Model | | Product Specification PS-42022-0001 (PDF) | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | Ser |
| General | | | image - Reference only |
| Product Family | | Crimp Terminals | |
| Series | | 42023 | EU RoHS China RoHS |
| Application | | 42023 Power | ELV and RoHS |
| Crimp Quality Equipm | ent | Yes | Compliant |
| Overview | lent | mlx | REACH SVHC |
| Product Name | | MLX™ | Contains SVHC: No Low-Halogen Status |
| Dhysical | | | Low-Halogen |
| Physical Gender | | Male | Need more information on product |
| Material - Metal | | Brass | environmental compliance? |
| Material - Plating Mat | na | Tin | |
| Material - Plating Mating Material - Plating Termination | | Tin | Email productcompliance@molex.com |
| Packaging Type | | Reel | For a multiple part number RoHS Certificate |
| Plating min - Mating | | 0.508µm (20µ") | Compliance, <u>click here</u> |
| | | 0.508µm (20µ") | |
| Plating min - Termination | | Crimp or Compression | Please visit the <u>Contact Us</u> section for any |
| Termination Interface: Style Wire Insulation Diameter | | 1.52-3.30mm (.060130") | non-product compliance questions. |
| Wire Size AWG | ler | | |
| Wire Size MWG | | 14, 16, 18, 20 N/A | |
| Material Info | | | Search Parts in this Series |
| Old Part Number | | 42023-2A1 | <u>42023</u> Series |
| Reference - Draw | ving Numbers | | Application Tooling FAQ |
| Product Specification | | PS-42022-0001 | Tooling specifications and manuals are |
| Sales Drawing | | SD-42023-**** | found by selecting the products below. |
| | | | Crimp Height Specifications are then |
| | | | contained in the Application Tooling |
| | | | Specification document. |
| | | | Global |
| | | | Description Product # |
| | | | Hand Crimp Tool 0638116800 |
| | | | for MLX™ Pin |
| | | | and Socket Crimp |
| | | | Terminals |
| | | | Extraction Tool 0011010168 |
| | | | FineAdjust™ <u>0639007500</u> |
| | | | Applicator for MXL [™] |
| | | | Crimp Terminals, |
| | | | 14-20 AWG wire with |
| | | | 2.08 to 2.50mm dia. |
| | | | Insulation |
| | | | FineAdjust™ <u>0639009800</u> |
| | | | Applicator for MXL [™] |
| | | | Crimp Terminals, |
| | | | 14-20 AWG wire with |

2.41 to 2.95mm dia. Insulation FineAdjust™ <u>0639009900</u> Applicator for MXL[™] Crimp Terminals, 14-20 AWG wire with 2.65 to 3.30mm dia. Insulation Tooking Kit for <u>(</u> MiniFit Compliant Pin 0639107500 Insertion T2 Terminator 0639109800 Tooling Die for MLX[™] Crimp Terminals, 14-20 AWG T2 Terminator 0639109900 Tooling Die for MLX[™] Crimp Terminals, 14-20 AWG

This document was generated on 06/02/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION