



### 192-103LEW-A01 Discrete Thermistors

(Home : Products)



192 Series, Uni-Curve with bare leads and epoxy, 10,000 Ohm resistance,  $\pm 1,0$  °C [1.8 °F] tolerance, 25/85 BETA = 3974

*Actual product appearance may vary.*

#### Description

192 Series Thermistors are high quality, low-cost, resistance temperature-matched interchangeable units. They offer additional cost savings by eliminating the need for individual resistance temperature calibration, as well as standardization of circuit components and simplification of design and replacement problems.

#### Features

##### Features

- Resistance temperature curve interchangeability
- Accuracy
- High stability
- Long life
- Cost effective
- Small size
- Epoxy coated

#### Potential Applications

##### Potential Applications

- Temperature measurement, indication and control
- Compensation of ambient temperature effects on copper coils, transistors, integrated circuits and other semiconductor devices
- Medical

### Product Specifications

Availability	Global
Resistance	10,000 Ohm
Tolerance	$\pm 1,0$ °C [1.8 °F]
Accuracy	0 °C to 70 °C [32 °F to 158 °F]
Beta	3974
Operating Temperature	-60 °C to 150 °C [-76 °F to 302 °F]
Diameter	2,413 mm [0.095 in]
Termination Material	32 Gauge tinned copper, alloy 180
Lead Length	38,1 mm [1.50 in]
Time Constant in Air	15.0 s
Dissipation Constant	0,75 m/W°C
Series Name	192