

ENGLISH 日本語 中文 한국어

Search: --Any--

Go

Company News Investors Careers Contact Login

Industries **Products** Brands Reference Support Sales and Distribution

Products


Products

[Product Type Search](#)[Parameter Search](#)[Threat Search](#)[Check Distributor](#)[Inventory](#)[Competitor Part Number](#)[Obsolete Parts](#)[Order Samples](#)[Product News](#)[New Products and Promotions](#)Part: **V321DA40**Series: [DA SERIES - HIGH ENERGY INDUSTRIAL VARISTOR](#)

Technology:: Metal Oxide Varistor

PARAMETERS

Key

PACKAGE TYPE	PKG TYPE	Packaged
MOUNT METHOD	MOUNT	Bolt-down
DISC DIAMETER	SIZE	40
RATED AC VOLTAGE	V_{MAC} (V)	320
CONTINUOUS DC VOLTAGE	V_{MDC} (V)	420.0
MAXIMUM NON-REPETITIVE SURGE ENERGY	W_{TM}	460.00
MAXIMUM NON-REPETITIVE SURGE CURRENT	I_{TM} NON-REPETITIVE (A)	40000
MAXIMUM SURGE CURRENT	I_{TM} (A)	0
MINIMUM VARISTOR VOLTAGE AT 1MA DC TEST CURRENT	V_{NOM} MIN	462.00
NOMINAL VOLTAGE	V_{NDC} (V)	510.00
MAXIMUM VARISTOR VOLTAGE AT 1MA DC TEST CURRENT	V_{NOM} MAX	561.00
CLAMPING VOLTAGE	V_C (V)	830
PEAK CURRENT	I_{PK} (A)	0.00
TYPICAL CAPACITANCE AT 1MHZ	TYP CAPACITANCE	3800
DUTY CYCLE SURGE RATING 3KA (8X20μS) # PULSES	3KA SURGE	0
DUTY CYCLE SURGE RATING 750A (8X20μS) # PULSES	750A SURGE	0
CLAMPING POLARITY	CLAMP POLARITY	Bi-directional
PACKAGE SIZE	PKG SIZE	40
BATTERY/SYSTEM VOLTAGE 12/14	VOLT 12/14	
BATTERY/SYSTEM VOLTAGE 24/28	VOLT 24/28	
BATTERY/SYSTEM VOLTAGE 36/42	VOLT 36/42	
CERTIFICATIONS	CERT	

CHECK DISTRIBUTOR STOCK [\[CHECK\]](#)REQUEST A SAMPLE [\[ADD TO CART\]](#)

Lightning Transients
AC Mains
Other Threats
Inductive Switching / Commutative Spikes



Series Datasheets



DA/DB Data Sheet

DA_DB.pdf (194 K)

Last Updated: May 16, 2005